

OUTDOOR STEP LIGHTS



LIGHT POINT FOR GARDENS AND FLOWERBEDS




Surface
installation



Installation flush
with ground




ICE LED 1.0



POWER / MODEL CODE	1W 350mA LE1011 ■ D A V - ■
LED COLOR	F - 2700K 5 - 3000K 9 - 4000K 0 - 5000K 1 - blue
POWER CABLES	includes 4.92 ft neoprene cable H05RN-F 2x0.01/0.75 Ø0.25 in 1 - 16.40 ft 2 - 32.81 ft 3 - 49.21 ft 4 - 65.62 ft
OPTICS	diffuse

LUMEN OUTPUT AT SOURCE	110 lm (3000K, 350mA)
DELIVERED LUMEN OUTPUT	89 lm (3000K, 350mA)
NO. AND TYPE OF LED	1 power LED 1/4 ANSI BIN (white LED colour) 50000h L90 B10 (Ta 25°C)
MATERIAL	body in anodized aluminum and sandblasted glass
POWER SUPPLY UNIT	Remote power supply required, not included
WIRING	series
MOUNTING	recessed (wall, ground) surface mounted (ground)
ACCESSORIES	see accessories page
NOTES	certified ETL version available on request

ICE LED 1.1




POWER / MODEL CODE	1W 350mA LE1111 ■ D A V - ■
LED COLOR	F - 2700K 5 - 3000K 9 - 4000K 0 - 5000K 1 - blue
POWER CABLES	includes 4.92 ft neoprene cable H05RN-F 2x0.01/0.75 Ø0.25 in 1 - 16.40 ft 2 - 32.81 ft 3 - 49.21 ft 4 - 65.62 ft
OPTICS	diffuse

LUMEN OUTPUT AT SOURCE	110 lm (3000K, 350mA)
DELIVERED LUMEN OUTPUT	89 lm (3000K, 350mA)
NO. AND TYPE OF LED	1 power LED 1/4 ANSI BIN (white LED colour) 50000h L90 B10 (Ta 25°C)
MATERIAL	body in anodized aluminum and sandblasted glass
POWER SUPPLY UNIT	Remote power supply required, not included
WIRING	series
MOUNTING	recessed (wall, ground) surface mounted (ground)
ACCESSORIES	see accessories page
NOTES	certified ETL version available on request




ACCESSORIES

ACCESSORIES FOR INSTALLATION

**WC0410**

Outer casing
(Ice LED 1.0)

**WC0411**

Outer casing
(Ice LED 1.1)

ICE LED

OUTDOOR STEP LIGHTS

ICE LED 1.0 1.1

