

Invisible is a square indoor recessed flush mounted luminaire made of AirCoral® which is suitable for installation on plasterboard or brick walls and ceilings. It is available in 3000K standard with a 40° optic.



## TECHNICAL DATA


<b>Wattage / Input</b>	9W (500mA)
<b>Power Supply</b>	Remote, not included. See page 2.
<b>Construction</b>	Body: AirCoral® Lens: Frosted Glass
<b>CCT</b>	2700K, 3000K, 4000K
<b>CRI</b>	>90
<b>Delivered Lumens</b>	557 lm (3000K)
<b>Efficacy</b>	61.9 lm/W
<b>Optics</b>	40°
<b>Finishes</b>	AirCoral® - suitable for painting
<b>LED Source</b>	Professional COB LED
<b>Fixture Dimensions</b>	7.48" l x 2.76" w x 9.65" h
<b>Cut-out Dimension</b>	7.68" x 7.28"
<b>Aperature</b>	3.94" x 3.94"
<b>Fixture Weight</b>	3.31 lbs
<b>IP Rating</b>	IP40

The body is made of AirCoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for AirCoral® calculator.

Additionally, AirCoral® is:

- Antibacterial.
- Antifungal.
- Scratch-resistant.
- Dust-resistant.
- Suitable for painting.
- LEED recognized material.

Fixture Dimensions



## ORDERING INFORMATION

Example: BU6133.Z.27.AC.US. Power Supplies ordered separately.

BU6133.Z		AC	US
<b>Model No.</b>	<b>CCT</b>	<b>Finish</b>	
BU6133.Z	27 - 2700K 30 - 3000K 40 - 4000K	AC - AirCoral®	US

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

500mA

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00469</a>	Phase Dim (120V only)	120VAC to 500mA, 14W, Class 2	1-1
<a href="#">PPLT00467-P</a>	0-10V Dimming to 1.0%	120-277VAC to 500mA, 50W, Class 2, DAMP	1-3
<a href="#">PPLT00561-P</a>	0-10V Dimming to 0.1%	120-277VAC to 500mA, 100W, Class 2	1-3

## Suggested Lutron Compatible


Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
<a href="#">PPLT00259</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 500mA, 10W, Class 2	1-1
<a href="#">PPLT00195</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 500mA, 19W, Class 2	1-1
<a href="#">PPLT00180</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 500mA, 27W, Class 2	2-2

For other power supply options consult factory.

## PHOTOMETRIC DATA

Note all Photometry is 3000K

Maximum Candela = 685



Job Name/Date:

Fixture Type Designation: