

LAM PHANTOM RECTANGLE

LIGHT ATMOTION
LAM32
IDEAS BECOMING LIGHT

miniMAXIMUM
LED LIGHT SYSTEMS

designplan®

datasheet


LAM Phantom Rectangle is a wall or ceiling mounted LED luminaire which delivers uniformity of light distribution and performance. It comes in 5 standard finishes and 3 sizes that can be used to create unique combinations on its own or with other Phantom shapes. **ADA compliant.**

TECHNICAL DATA

Wattage / Input	4.5W, 13W, 19.5W
Power Supply	Remote 24VDC, not included. See page 2.
Construction	Body: Aluminum Lens: Extra Clear Acrylic Cable Length: 1.64'
CCT	2700K, 3000K, 4000K
BUG Rating	B0-U2-G0
Delivered Lumens	664 lm (3000K - Phantom Rectangle 1) 1992 lm (3000K - Phantom Rectangle 2) 2988 lm (3000K - Phantom Rectangle 3)
Efficacy	147.6 lm/W (3000K - Rectangle 1) 153.2 lm/W (3000K - Rectangle 2) 153.2 lm/W (3000K - Rectangle 3)
Optics	Diffuse
Finishes	5 Standard, See Below
Fixture Dimensions	7.8" l x 3.9" w x 2.4" h (Rectangle 1) 15.6" l x 7.8" w x 2.4" h (Rectangle 2) 23.6" l x 11.8" w x 2.4" h (Rectangle 3)
Color Consistency	<3-Step MacAdam
IP Rating	IP65
Impact Resistance	IK07



Fixture Dimensions - See page 2



ORDERING INFORMATION

Example: LM01.104452.US.01.DI.BP.

		DI	
Model No.	Finish	Optic	CCT
LM01.104452.US (Rectangle 1 - 4.5W)	01 - White	DI - Diffuse	BC - 2700K
LM01.104453.US (Rectangle 2 - 13W)	02 - Black		BP - 3000K
LM01.104454.US (Rectangle 3 - 19.5W)	03 - Gray		BF - 4000K
	04 - Cor-ten		
	11 - Anthracite		

Job Name/Date:

Fixture Type Designation:

LAM PHANTOM RECTANGLE


LIGHT ATMOTION
LAM32
IDEAS BECOMING LIGHT

mini M MAXIMUM
LIFE LONG SUPPORT


designplan®

datasheet


FIXTURE DIMENSIONS



3.94" x 7.87" x H2.36"



7.87" x 15.75" x H2.36"



11.81" x 23.62" x H2.36"

SUGGESTED POWER SUPPLIES

Remote 24VDC Driver in NEMA Enclosure - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures		
			4.5W	13W	19.5W
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-17	1-5	1-3


For other power supply options consult factory.

PHOTOMETRIC DATA

Rectangle 1

Maximum Candela = 192.0

— C0 - C180
— C90 - C270




PHOTOMETRIC FILENAME : PHANTOM RECTANGLE 1 LM01.104452.XX.DI.XX 3.9X7.9IN.IES

Rectangle 2

Maximum Candela = 192.0

— C0 - C180
— C90 - C270




PHOTOMETRIC FILENAME : PHANTOM RECTANGLE 2 LM01.104453.XX.DI.XX 7.9X15.8IN.IES

Rectangle 3

Maximum Candela = 192.0

— C0 - C180
— C90 - C270



PHOTOMETRIC FILENAME : PHANTOM RECTANGLE 3 LM01.104454.XX.DI.XX 11.8X23.6IN.IES

Job Name/Date:

Fixture Type Designation: