


MIN / MAX - TRIANGOLO 1 IP68

SUITABLE FOR USE IN FOUNTAINS or POOLS

MIN / MAX Triangolo 1 are triangular, IP68-rated LED luminaires for flush installation in fountains or swimming pools, both indoors or outdoors - submersible to 1 m (3.28'). Triangolo is available in 2 different shapes - each in 5 sizes with sandblasted or antislip glass. Pressure switch on request. Can be ordered in aluminum IP67 version for in-grade non-fountain use.



Fixture Dimensions - See page 2

TECHNICAL DATA

Wattage / Input	16W, 33W, 45W, 60W, 76W
Power Supply	Remote, not included. Consult Factory.
Construction	Body: Stainless Steel Lens: Extra Clear Tempered Glass Cable Length: 1.64'
CCT	2700K, 3000K, 4000K (RGBW or Tunable White on request)
BUG Rating	B0-U0-G0
Delivered Lumens	1360-6800 lm (3000K)
Efficacy	83-89.5 lm/W (3000K)
Optics	Diffuse
Finishes	Sandblasted or Antislip Glass
Fixture Dimensions <i>(all are 1.6" h)</i>	9.8" x 15.9" x 15.9" (T1) 19.7" x 31.9" x 31.9" (T2) 29.5" x 47.3" x 47.3" (T3) 39.4" x 63.8" x 63.8" (T4) 49.2" x 79.7" x 79.7" (T5)
Color Consistency	3-Step MacAdam
IP Rating	IP68 - Submersible to 5 m (16.4')
Impact Resistance	IK10
Driveover Capacity	Up to 11,000 lbs



ORDERING INFORMATION

Example: LM07.103913.US.A1.DI.BP. Accessories / Power Supplies ordered separately.

<input type="text"/>	<input type="text"/>	DI	<input type="text"/>
Model No.	Finish	Optic	CCT
LM07.103853.US (T1 - 16W)	60 - Sandblasted	DI - Diffuse	BC - 2700K
LM07.103854.US (T2 - 33W)	A1 - Antislip		BP - 3000K
LM07.103855.US (T3 - 45W)			BF - 4000K
LM07.103912.US (T4 - 60W)			
LM07.103913.US (T5 - 76W)			

Job Name/Date:

Fixture Type Designation:

MIN / MAX - TRIANGOLO 1 IP68

SUITABLE FOR USE IN FOUNTAINS or POOLS


LIGHT ATMOTION
LAMB2
IDEAS BECOMING LIGHT

minima M AXIMUM

designplan®

datasheet

FIXTURE DIMENSIONS



SUGGESTED POWER SUPPLIES

Consult Factory

ACCESSORIES - Installation



LM20.103979 (T1 - 10.2" x 16.3" x 3.9" h)

LM20.103980 (T2 - 20.0" x 32.2" x 3.9" h)

LM20.103981 (T3 - 29.8" x 48.1" x 3.9" h)

LM20.103982 (T4 - 39.7" x 64.1" x 3.9" h)

LM20.103983 (T5 - 49.5" x 80.0" x 3.9" h)

IP68 Housing

LM20.104765

Light Source Extraction Tool Kit

(For T1, T2, T6, T7)

LM20.104812

Light Source Extraction Tool Kit

(For T3, T4, T5, T8, T9, T10)

Job Name/Date:

Fixture Type Designation:

MIN / MAX - TRIANGOLO 1 IP68

SUITABLE FOR USE IN FOUNTAINS or POOLS

LIGHT ATMOTION
LAMBDA
IDEAS BECOMING LIGHT

minima M AXIMUM


designplan®

datasheet

PHOTOMETRIC DATA

T1-T10

Maximum Candela = 268.3



PHOTOMETRIC FILENAME : T1-T10-all the same.IES

Job Name/Date:

Fixture Type Designation: