MAXI BILD

Maxi Bild is a square recessed downlight made of Coral[®], suitable for indoor installation on ceilings where it becomes an integral part of the surface. It has a rearward frosted glass lens and is available in 3000K standard with a 40° optic and a 90° light beam inclination.

TECHNICAL DATA


Wattage / Input	27W (700mA)	
Power Supply	Remote, not included. See page 2.	
Construction	Body: Coral®	
	Lens: 0.39" Rearward Frosted Glass	
ССТ	3000K (2700K, 4000K on request)	
CRI	>90	
Delivered Lumens	1711 lm (3000K)	
Efficacy	63.4 lm/W	
Optics	40°	
Finishes	Coral [®] Plaster	
Fixture Dimensions	9.06" l x 9.06" w x 5.31" h	
Cut-out Dimension	9.45" x 9.45"	
Aperature	6.89" x 6.89"	
Fixture Weight	6.61 lbs	
IP Rating	IP40	


designplan@

datasheet



Fixture Dimensions





The body is made of Coral $\ensuremath{\textcircled{B}}$ a unique patented composite material made from natural minerals and aggregating elements.

Additionally, Coral® is:

Extreme resistance to high temperatures and thermal shock. Highly impervious to knocks and scratches. Can easily be decorated with any type of paint (water or spirit based). Made of non-toxic materials and is non-allergic. Does not produce fumes, even in case of fire. Naturally dust repellent.

ORDERING INFORMATION

Example: BU4411.00.30.US. Accessories / Power Supplies ordered separately.

BU4411	. 00].	US
Model No.	Finish	ССТ	
BU4411	00 - Coral®	30 - 3000K (standard) 27 - 2700K (on request) 40 - 4000K (on request)	US

Job Name/Date:

Fixture Type Designation:

datasheet

SUGGESTED POWER SUPPLIES

700mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00480-P	0-10V Dimming to 1.0%	120-277VAC to 700mA, 30W, Class 2, DAMP	1-1
PPLT00261	Leading / Trailing-Edge Dimming to 10% (120V only)	120-277VAC to 700mA, 32W, Class 2	1-1
PPLT00467-P 0-10V Dimming to 1.0%		120-277VAC to 700mA, 50W, Class 2	1-1

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00181	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 700mA, 38W, Class 2	1-1


For other power supply options consult factory.

ACCESSORIES

Installation - Consult Factory for Back Box

PHOTOMETRIC DATA

Note: All Photometry is 3000K



PHOTOMETRIC FILENAME : MAXI BILD LED BU4411.00.IES

Job Name/Date:

Fixture Type Designation: