

NANO IP20

INDOOR

Fix (not adjustable) 0° - 0°

2.80" × 5.43"

Material : CALCYT® plaster

NANO LED DIM 100 LM

REF N° 151 60 500 CRI 80 warm white 2200°K

REF N° 151 60 000 CRI 90 warm white 2700°K

REF N° 151 60 100 CRI 90 warm white 3000°K

REF N° 151 60 200 CRI 90 neutral white 4000°K

REF N° 151 60 300 royal blue

1W - excl. LED driver - current

controlled 350mA - 

Ⓟ - serial wiring - 3 Step MacAdam

Requires remote LED driver - 350mA

NANO LED DIM 200 LM

REF N° 151 62 500 CRI 80 warm white 2200°K

REF N° 151 62 000 CRI 90 warm white 2700°K

REF N° 151 62 100 CRI 90 warm white 3000°K

REF N° 151 62 200 CRI 90 neutral white 4000°K

REF N° 151 62 300 royal blue

2W - excl. LED driver - current

controlled 350mA - 

Ⓟ - serial wiring - 3 Step MacAdam

Requires remote LED driver - 350mA

NANO LED DIM 400 LM

REF N° 151 61 500 CRI 80 warm white 2200°K

REF N° 151 61 000 CRI 90 warm white 2700°K

REF N° 151 61 100 CRI 90 warm white 3000°K

REF N° 151 61 200 CRI 90 neutral white 4000°K


REF N° 151 61 300 royal blue

4W - excl. LED driver - current

controlled 350mA - 

Ⓟ - serial wiring - 3 Step MacAdam

Requires remote LED driver - 350mA



Ready for installation in solid walls
Optional plasterkit for installation into gypsum walls

PLASTERKIT NANO

REF N° 751 01 000 For mounting into gypsum walls

Housing: perforated aluminium

designplan® 

79 Trenton Avenue
Frenchtown, NJ 08825

Tel: (908) 996-7710
Fax: (908) 996-7042