

NEVA 2 SERIES

NEVA 2.0, 2.1, 2.2 and MINI 2

The Neva 2 series are linear profiles with deep-set optics perfect for architectural lighting for both indoor and outdoor applications. Available in 4 different lengths with ingrade housing for recessed applications or adjustable brackets for surface mount.

TECHNICAL DATA

Wattage / Input	See Chart on page 2. (24VDC)
Power Supply	Remote, not included. See page 3.
Construction	Body: Anodized Aluminum Lens: Tempered and Serigraphed Glass Cable Length: 4.92' standard
CCT	2700K, 3000K, 4000K
CRI	CRI >80
Delivered Lumens	See Chart on page 2.
Efficacy	62-66 lm/W
Optics	11°, 30°, 45°, 10°x40°
Finishes	N/A
Cut-Out Dimensions	See Chart on page 2.
Fixture Dimensions	See Chart on page 2.
Fixture Weight	See Chart on page 2.
LED Source	See Chart on page 2.
Lumen Maintenance	L85, B10>50,000hrs
Color Consistency	3-Step MacAdam
Operating Temp.	-4°F to +113°F
IP Rating	IP67
Impact Rating	IK06



ORDERING INFORMATION

Example: NV22005MA or NV22005MA-3. Accessories / Power Supplies ordered separately.

Model No.	CCT	Optics	Finish	Cable Length
NV0200 - Neva Mini 2 (5.5W)	F - 2700K	S - 11°	A - Aluminum	4.92' standard
NV0201 - Neva Mini 2 (7.5W)	5 - 3000K	M - 30°		1 - 16.40'
NV2000 - Neva 2.0 (11W)	9 - 4000K	L - 45°		2 - 32.81'
NV2001 - Neva 2.0 (15W)		W - 10°x40°		3 - 49.21'
NV2100 - Neva 2.1 (16W)				4 - 65.62'
NV2101 - Neva 2.1 (22W)				
NV2200 - Neva 2.2 (27W)				
NV2201 - Neva 2.2 (38W)				

Job Name/Date:


Fixture Type Designation:

NEVA 2 SERIES


NEVA 2.0, 2.1, 2.2 and MINI 2

TECHNICAL DATA


	NEVA MINI 2		NEVA 2.0		NEVA 2.1		NEVA 2.2	
Wattage	5.5W	7.5W	11W	15W	16W	22W	27W	38W
Delivered Lumens (3000K)	345 lm	483 lm	690 lm	966 lm	1035 lm	1450 lm	1725 lm	2415 lm
Fixture Dim. (l,w,h)	12.44" x 1.46" x 2.28"		26.65" x 1.46" x 2.28"		40.83" x 1.46" x 2.28"		69.21" x 1.46" x 2.28"	
Alum. Housing Dim. (l,w,h) & Cut-Out Size (l,w)	12.68" x 1.65" x 3.31" same as housing		26.85" x 1.65" x 3.31" same as housing		41.02" x 1.65" x 3.31" same as housing		69.41" x 1.65" x 3.31" same as housing	
Alum Housing Dim. (l,w,h) (for plasterboard) & Cut-Out Size (l,w)	12.68" x 1.65" x 3.31" same as housing		26.85" x 1.65" x 3.31" same as housing		41.02" x 1.65" x 3.31" same as housing		69.41" x 1.65" x 3.31" same as housing	
Fixture Weight	1.28 lbs		2.76 lbs		4.12 lbs		6.94 lbs	
LED Source	3 power LEDs, LED spacing 4.72"		6 power LEDs, LED spacing 4.72"		9 power LEDs, LED spacing 4.72"		15 power LEDs, LED spacing 4.72"	




NEVA MINI 2



NEVA 2.0



NEVA 2.1



NEVA 2.2

Job Name/Date:

Fixture Type Designation:

NEVA 2 SERIES

NEVA 2.0, 2.1, 2.2 and MINI 2

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures / Power Supply							
			Neva Mini 2		Neva 2.0		Neva 2.1		Neva 2.2	
			5.5W	7.5W	11W	15W	16W	22W	27W	38W
PPLT00632	0-10V Dimming (Dim to Off)	120-277VAC to 24VDC, 12W, Class 2	1-1	1-1	-	-	-	-	-	-
PPLT00157	Non-Dim	120VAC to 24VDC, 60W	1-8	1-6	1-4	1-3	1-3	1-2	1-1	1.1
PPLT00599	ELV / TRIAC & 0-10V Dimming (100 to 0%)	120-277VAC to 24VDC, 96W, Class 2	1-13	1-10	1-6	1-5	1-4	1-3	1-2	1-2
PPLT00284	Non-Dim	120-277VAC to 24VDC, 100W	1-14	1-10	1-7	1-5	1-5	1-3	1-2	1-2
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W	2-14	2-10	1-7	1-5	1-5	1-3	1-2	1-2

For other power supply options consult factory.


Job Name/Date:

Fixture Type Designation:


NEVA 2 SERIES

NEVA 2.0, 2.1, 2.2 and MINI 2


ACCESSORIES - Installation



Aluminum Outer Casing
WC6500 - Neva Mini 2 (12.68")
WC6520 - Neva 2.0 (26.85")
WC6521 - Neva 2.1 (41.02")
WC6522 - Neva 2.2 (69.41")



Aluminum Outer Casing
For plasterboard applications
WC6700 - Neva Mini 2 (12.68")
WC6720 - Neva 2.0 (26.85")
WC6721 - Neva 2.1 (41.02")
WC6722 - Neva 2.2 (69.41")




WN6005 - Alignment Kit
 For Aluminum Outer Casings




WN6001 - Fixture Anti Fall Kit
 Optional for Ceiling (and if desired Wall) Installations

Anti-Glare




Honeycomb Louver
WH6002 - Neva Mini 2
WH6020 - Neva 2.0
WH6021 - Neva 2.1
WH6022 - Neva 2.2



Anti-Glare Shield
 Stainless steel painted black
WB6500 - Neva Mini 2 (12.91")
WB6520 - Neva 2.0 (26.50")
WB6521 - Neva 2.1 (40.67")
WB6522 - Neva 2.2 (69.06")

Spare Parts



WN6002 - Brackets
 Pair of U-Shaped Brackets



WN6003 - Springs
 Pair of Spring



WN6006 - Extractors
 Pair of extractors for outer casings

Job Name/Date:

Fixture Type Designation:

NEVA 2 SERIES


NEVA 2.0, 2.1, 2.2 and MINI 2

PHOTOMETRIC DATA


Note all Photometry is CRI 80, 3000K

NEVA MINI 2


S - 11°




M - 30°



L - 45°




W - 12°x40°




NEVA 2.0


S - 11°




M - 30°



L - 45°



W - 12°x40°



Job Name/Date:

Fixture Type Designation: