

NEVA 2 SURFACE

NEVA 2.0, 2.1, 2.2 and MINI 2

The Neva 2 series are linear profiles with deep-set optics perfect for architectural lighting for both indoor and outdoor applications. Available in 4 different lengths with ingrade housing for recessed applications or adjustable brackets for surface mount.

TECHNICAL DATA

Wattage / Input	See Chart on page 2. (24VDC)
Power Supply	Remote, not included. See page 3.
Construction	Body: Anodized Aluminum Lens: Tempered and Serigraphed Glass Cable Length: 4.92' standard
CCT	2700K, 3000K, 4000K
CRI	CRI >80
Delivered Lumens	See Chart on page 2.
Efficacy	62-66 lm/W
Optics	11°, 30°, 45°, 10°x40°
Finishes	N/A
Cut-Out Dimensions	See Chart on page 2.
Fixture Dimensions	See Chart on page 2.
Fixture Weight	See Chart on page 2.
LED Source	See Chart on page 2.
Lumen Maintenance	L85, B10>50,000hrs
Color Consistency	3-Step MacAdam
Operating Temp.	-4°F to +113°F
IP Rating	IP67
Impact Rating	IK06



ORDERING INFORMATION

Example: NV22005MA or NV22005MA-3. Accessories / Power Supplies ordered separately.

			A	
Model No.	CCT	Optics	Finish	Cable Length
NV0200 - Neva Mini 2 (5.5W)	F - 2700K	S - 11°	A - Aluminum	4.92' standard
NV0201 - Neva Mini 2 (7.5W)	5 - 3000K	M - 30°		1 - 16.40'
NV2000 - Neva 2.0 (11W)	9 - 4000K	L - 45°		2 - 32.81'
NV2001 - Neva 2.0 (15W)		W - 10°x40°		3 - 49.21'
NV2100 - Neva 2.1 (16W)				4 - 65.62'
NV2101 - Neva 2.1 (22W)				
NV2200 - Neva 2.2 (27W)				
NV2201 - Neva 2.2 (38W)				

Job Name/Date:


Fixture Type Designation:

NEVA 2 SURFACE


NEVA 2.0, 2.1, 2.2 and MINI 2

TECHNICAL DATA


	NEVA MINI 2		NEVA 2.0		NEVA 2.1		NEVA 2.2	
Wattage	5.5W	7.5W	11W	15W	16W	22W	27W	38W
Delivered Lumens (3000K)	345 lm	483 lm	690 lm	966 lm	1035 lm	1450 lm	1725 lm	2415 lm
Fixture Dim. (l,w,h)	12.44" x 1.46" x 2.28"		26.65" x 1.46" x 2.28"		40.83" x 1.46" x 2.28"		69.21" x 1.46" x 2.28"	
Fixture Weight	1.28 lbs		2.76 lbs		4.12 lbs		6.94 lbs	
LED Source	3 power LEDs, LED spacing 4.72"		6 power LEDs, LED spacing 4.72"		9 power LEDs, LED spacing 4.72"		15 power LEDs, LED spacing 4.72"	




NEVA MINI 2



NEVA 2.0



NEVA 2.1



NEVA 2.2

Job Name/Date:

Fixture Type Designation:

NEVA 2 SURFACE

NEVA 2.0, 2.1, 2.2 and MINI 2

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures / Power Supply							
			Neva Mini 2		Neva 2.0		Neva 2.1		Neva 2.2	
			5.5W	7.5W	11W	15W	16W	22W	27W	38W
PPLT00586	Non-Dim	120-277VAC to 24VDC, 40W, Class 2	1-5	1-4	1-2	1-2	1-2	1-1	1-1	-
PPLT00681	Non-Dim	120-277VAC to 24VDC, 90W, Class 2, IP67	1-13	1-9	1-6	1-4	1-4	1-3	1-2	1-1
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W	2-14	2-10	1-7	1-5	1-5	1-3	1-2	1-2

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures / Power Supply							
						Neva Mini 2		Neva 2.0		Neva 2.1		Neva 2.2	
						5.5W	7.5W	11W	15W	16W	22W	27W	38W
PPLT00530	L3DAE / L3D0	L3DA/L3D0	100%-1%	Hi-Lume™ 0.1% EcoSystem™ or 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-13	1-10	1-6	1-5	1-4	1-3	1-2	1-2

DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures							
			Neva Mini 2		Neva 2.0		Neva 2.1		Neva 2.2	
			5.5W	7.5W	11W	15W	16W	22W	27W	38W
PPLT00715	ELV / TRIAC / 0-10V Dimming	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-13	1-10	1-6	1-5	1-4	1-3	1-2	1-2

For other power supply options consult factory.


Job Name/Date:

Fixture Type Designation:

NEVA 2 SURFACE


NEVA 2.0, 2.1, 2.2 and MINI 2

ACCESSORIES - Installation



WM0601


Pair of brackets 2.95" h



WM0602

Pair of brackets 5.51" h

Anti-Glare



Honeycomb Louver

WH6002 - Neva Mini 2

WH6020 - Neva 2.0

WH6021 - Neva 2.1

WH6022 - Neva 2.2



Anti-Glare Shield

Stainless steel painted black

WB6500 - Neva Mini 2 (12.91")

WB6520 - Neva 2.0 (26.50")

WB6521 - Neva 2.1 (40.67")

WB6522 - Neva 2.2 (69.06")

Job Name/Date:

Fixture Type Designation:

NEVA 2 SURFACE


NEVA 2.0, 2.1, 2.2 and MINI 2

PHOTOMETRIC DATA


Note all Photometry is CRI 80, 3000K

NEVA MINI 2


S - 11°




L - 45°



M - 30°




W - 12°x40°




NEVA 2.0


S - 11°




L - 45°



M - 30°



W - 12°x40°



Job Name/Date:

Fixture Type Designation: