

NEVA 4 RECESSED

NEVA 4.0, 4.1, 4.2

The Neva 4 series are linear profiles with deep-set optics and a built-in power supply which has an in-out connection system so that the fixtures can be installed in a line. Available in 3 different lengths with in-grade housing for recessed applications or adjustable brackets for surface mount. Neva are perfect for architectural lighting in both indoor and outdoor applications.

TECHNICAL DATA

Wattage / Input	See Chart on page 2 (120VAC)
Power Supply	Integral - On/Off or 0-10V
Construction	Body: Black Anodized Aluminum Lens: Serigraphed, Tempered, Transparent, Extra-clear Glass
CCT	2700K, 3000K, 4000K
CRI	>80
Delivered Lumens	See Chart on page 2.
Efficacy	61.5-70 lm/W
Optics	11°, 30°, 45°, 10°x40°
Finishes	Black Anodized Aluminum (4 Stage Marine Grade Finish)
Cut-Out Dimensions	See Chart on page 2.
Fixture Dimensions	See Chart on page 2.
Fixture Weight	See Chart on page 2.
LED Source	See Chart on page 2.
Lumen Maintenance	L85, B10>50,000hrs (Ta 25°C)
Color Consistency	3-Step MacAdam
Operating Temp.	-4°F to +113°F
IP Rating	IP65, IP67
Impact Rating	IK08



ORDERING INFORMATION

Example: NV40100V01F0SN. Accessories ordered separately.

					N
Model No.	Control System	Optical Accessory	CCT	Optics	Finish
NV4010 - Neva 4.0 (16W)	000 - ON/OFF	0 - None	F0 - 2700K	S - 11°	N - Black
NV4110 - Neva 4.1 (24W)	0V0 - 0-10V	1 - Honeycomb Louvre	50 - 3000K	M - 30°	Anodized
NV4210 - Neva 4.2 (40W)			90 - 4000K	L - 45°	
				W - 10°x40°	

Job Name/Date:




Fixture Type Designation:

NEVA 4 RECESSED

NEVA 4.0, 4.1, 4.2

TECHNICAL DATA

	NEVA 4.0	NEVA 4.1	NEVA 4.2
Wattage	16W	24W	40W
Delivered Lumens (3000K)	966 lm (3000K, 30°)	1450 lm (3000K, 30°)	2415 lm (3000K, 30°)
Fixture Dim. (l,w,h)	26.65" x 1.46" x 2.91"	40.83" x 1.46" x 2.91"	69.21" x 1.46" x 2.91"
Alum. Housing Dim. (l,w,h) & Cut-Out Size (l,w)	26.85" x 1.65" x 3.31" same as housing	41.02" x 1.65" x 3.31" same as housing	69.41" x 1.65" x 3.31" same as housing
Alum Housing Dim. (l,w,h) (for plasterboard) & Cut-Out Size (l,w)	26.85" x 1.65" x 3.31" same as housing	41.02" x 1.65" x 3.31" same as housing	69.41" x 1.65" x 3.31" same as housing
Fixture Weight	3.53 lbs	4.63 lbs	7.98 lbs
LED Source	6 power LEDs, LED spacing 4.72"	9 power LEDs, LED spacing 4.72"	15 power LEDs, LED spacing 4.72"




Job Name/Date:

Fixture Type Designation:

NEVA 4 RECESSED

NEVA 4.0, 4.1, 4.2

ACCESSORIES - Installation




Aluminum Outer Casing

WC6520 - Neva 4.0 (26.85")

WC6521 - Neva 4.1 (41.02")

WC6522 - Neva 4.2 (69.41")



Aluminum Outer Casing

For plasterboard applications

WC6720 - Neva 4.0 (26.85")

WC6721 - Neva 4.1 (41.02")

WC6722 - Neva 4.2 (69.41")



WN6005 - Alignment Kit

For Aluminum Outer Casings



WN6001 - Fixture Anti Fall Kit

Optional for Ceiling (and if desired Wall) Installations

Anti-Glare



Anti-Glare Shield


Stainless steel painted black

WB6520 - Neva 4.0 (26.50")

WB6521 - Neva 4.1 (40.67")

WB6522 - Neva 4.2 (69.06")

Spare Parts



WN6002 - Brackets

Pair of U-Shaped Brackets



WN6003 - Springs

Pair of Spring



WN6006 - Extractors

Pair of extractors for outer casings

Job Name/Date:

Fixture Type Designation:


NEVA 4 RECESSED

NEVA 4.0, 4.1, 4.2


PHOTOMETRIC DATA

Note all Photometry is CRI 80, 3000K


S - 11°




M - 30°



L - 45°



W - 10°x40°



Job Name/Date:

Fixture Type Designation: