

NIMBUS



Nimbus



OTHER AVAILABLE CODES

BU6281.27.AC	lens light color	40° 2700K
BU6281.40.AC	lens light color	40° 4000K (on request)
BU6283.27.AC	lens light color	120° 2700K
BU6283.40.AC	lens light color	120° 4000K (on request)

TECHNICAL FEATURES

Code	BU6281.AC	BU6283.AC
Type	Downlight 90°	Downlight 90°
Material	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	73.41 ft ²	73.41 ft ²
Weight	6.61 lbs	6.61 lbs
Mounting	Ceiling recessed	Ceiling recessed
IP rating	IP40	IP40
Control gear	ON/OFF driver (included)	Dimmable constant current driver (included)
Cut out for plasterboard	9.65 x 9.65 in	9.65 x 9.65 in
Lamp type	LED 1050mA	LED 500mA
Lamp wattage	1 x 40W	2 x 6.5W
Luminous efficacy	1 x 4680 lm - 3000K	2 x 930 lm - 3000K
Light distribution	Wide beam 40°	Wide beam 120°
Fitting	-	-
Light color	White 3000K	White 3000K
Light hole	6.89 x 6.89 in	6.89 x 6.89 in
Voltage connection	50/60Hz	50/60Hz
CRI	>90	>90
Note	Extra white satin glass. Frosted glass recessed 1.18 in into the ceiling. Other available light colors: 2700K, 4000K (on request).	Extra white satin glass. Frosted glass recessed 1.18 in into the ceiling. Trailing-edge and leading-edge dimming (20 - 100%). Other available light colors: 2700K, 4000K (on request).

OPTIONAL

Brick box	-	cod. BR6283LT
-----------	---	---------------

designplan®

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042