


PERISCOPE 02


The Periscope series are L-shaped outdoor bollards available in three different heights with asymmetric optics and 3 standard finishes. Offered with 120VAC - 0-10V Dimming or 120-277VAC - ON/OFF.



TECHNICAL DATA

Wattage	7W, 14W
Power Supply	Integral 120VAC (0-10V Dimming) or Integral 120-277VAC (ON/OFF)
Construction	Body: High Corrosion Resistance, Extruded Copper-free Aluminum Lens: Tempered Safety Glass Gasket: Silicone Screws: Stainless Steel
CCT	3000K, 4000K
Delivered Lumens	805 lm (3000K, 7W) 1,610 lm (3000K, 14W)
Efficacy	115 lm/W (3000K, 7W) 115 lm/W (3000K, 14W)
Optics	Asymmetric
Finishes	Textured Gray, Anthracite Gray, Matte Black
Fixture Dimensions	5.51" l x 7.09" w x 19.69" h
Fixture Weight	9.92 lbs
LED Source	4 CREE "XP-G2" LED (7W) 8 CREE "XP-G2" LED (14W)
IP Rating	IP65
Impact Rating	IK10

Fixture Dimensions



ORDERING INFORMATION


Example: 601603P-30K-ASM-AG-B.

	-		-	ASM	-		-	
Model No.		CCT		Optics		Finish		Dimming
601603P - 7W 601604P - 14W		30K - 3000K 40K - 4000K		ASM - Asymmetric		TG - Textured Gray AG - Anthracite Gray MB - Matte Black		A - 0-10V (120VAC) B - ON/OFF (120-277VAC)

Job Name/Date:

Fixture Type Designation:

ACCESSORIES - Installation




AM-0001
Anchor Base

PHOTOMETRIC DATA

7W


Maximum Candela = 293.2



PHOTOMETRIC FILENAME : PERISCOPE 02 7W 601603P.IES

14W

Maximum Candela = 610.7



PHOTOMETRIC FILENAME : PERISCOPE 02 14W 601604P.IES

Job Name/Date:

Fixture Type Designation: