

PICA ZERO IP20


Pica Zero is a recessed luminaire for use in walls as orientation lighting. It is available as an indoor (IP20), bathroom (IP54) or outdoor (IP54) version. Pica Zero differs from the other versions by a ring in the center of the fixture. It can be directly installed in solid walls, and gypsum walls with an optional plasterkit.



TECHNICAL DATA

Wattage / Input	1W, 2W, 4W (350mA)
Power Supply	Remote, not included. See page 2.
Construction	Body: Calcyt® Plaster Lens: Frosted Diffuser
CCT	2200K, 2700K, 3000K, 4000K, Royal Blue
CRI	>80 and >90
Optics	Fixed
Delivered Lumens	38 lm (1W, 3000K)
Efficacy	38 lm/W
Finishes	Paintable Plaster
Cut-Out Dimensions	5.20" x 5.20"
Fixture Dimensions	4.96" l x 4.96" w x 2.52"
Aperture	Ø3.39" Outer Ring Ø2.59" Inner Ring
Color Consistency	3-Step MacAdam
IP Rating	IP20

Wall Cut-Out: 5.20" x 5.20"
Fixture Dimensions



ORDERING INFORMATION

Example: 128 61 000. Accessories / Power Supplies ordered separately.

Model No.	Description	Model No.	Description
128 60 500 - 2200K	1W, 100 lm, CRI 80, IP20 Indoor	125 61 500 - 2200K	4W, 400 lm, CRI 80, IP20 Indoor
128 60 000 - 2700K	1W, 100 lm, CRI 90, IP20 Indoor	125 61 000 - 2700K	4W, 400 lm, CRI 90, IP20 Indoor
128 60 100 - 3000K	1W, 100 lm, CRI 90, IP20 Indoor	125 61 100 - 3000K	4W, 400 lm, CRI 90, IP20 Indoor
128 60 200 - 4000K	1W, 100 lm, CRI 90, IP20 Indoor	125 61 200 - 4000K	4W, 400 lm, CRI 90, IP20 Indoor
128 60 300 - Royal Blue	1W, 100 lm, IP20 Indoor	125 61 300 - Royal Blue	4W, 400 lm, IP20 Indoor
128 62 500 - 2200K	2W, 200 lm, CRI 80, IP20 Indoor		
128 62 000 - 2700K	2W, 200 lm, CRI 90, IP20 Indoor		
128 62 100 - 3000K	2W, 200 lm, CRI 90, IP20 Indoor		
128 62 200 - 4000K	2W, 200 lm, CRI 90, IP20 Indoor		
128 62 300 - Royal Blue	2W, 200 lm, IP20 Indoor		

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

350mA


Part Number	Description	Input/Output	# of Fixtures		
			1W	2W	4W
PPLT00138	0-10V Dimming to 10%	120-277VAC to 350mA, 4W, Class 2	2-3	1-1	N/A
PPLT00468	Phase Dim (120V only)	120VAC to 350mA, 14W, Class 2	4-13	2-6	1-3
PPLT00308-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 30W, Class 2	1-19	1-9	1-4
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 50W, Class 2	1-19	1-9	1-4
PPLT00538-P	0-10V Dimming to 0.1% (4 channels)	120-277VAC to 350mA, 100W, Class 2	1-20 (1-80)	1-10 (1-40)	1-5 (1-20)

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures		
						1W	2W	4W
PPLT00247	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driv.	120-277VAC to 350mA, 7W, Class 2	3-6	2-3	1-1
PPLT00516	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driv.	120-277VAC to 350mA, 13W, Class 2	6-13	3-6	2-3
PPLT00179	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driv.	120-277VAC to 350mA, 19W, Class 2	11-18	6-9	3-4

For other power supply options consult factory.

REQUIRED ACCESSORIES - Installation



725 01 000
Outer Casing

PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation: