PONTE GRANDE



datasheet





TECHNICAL DATA

standard with a 120° optic.

| Wattage / Input | 4W (120-277VAC) |
|--------------------|------------------------------|
| Power Supply | Integral |
| Construction | Body: AirCoral® |
| ССТ | 3000K |
| CRI | >90 |
| Delivered Lumens | 730 lm (3000K) |
| Efficacy | 182.5 lm/W |
| Optics | 120° |
| Finishes | AirCoral® |
| Fixture Dimensions | 17.72" l x 6.69" w x 3.54" h |
| Fixture Weight | - |
| IP Rating | IP20 |

Ponte Grande is a bidirectional surface mounted luminaire made of AirCoral® that is suitable for indoor installtion. It is available in 3000K as

The body is made of Aircoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for Aircoral® calculator.

Additionally, Aircoral® is:

Antibacterial.

Antifungal.


Scratch-resistant.

Dust-resistant.

Suitable for painting.

LEED recognized material.

Fixture Dimensions



PHOTOMETRIC DATA

Note all Photometry is 3000K

Maximum Candela = 156.3

- C0 - C180
- C90 - C270

117


117

78

Fixture Type Designation:

ORDERING INFORMATION

Example: BU7908.AC.US.



Job Name/Date:

P: 908-996-7710 F: 908-996-7042

1 of 1