

# Q1 48V


Q1 48V is a high performance projector for the 48V track system made of power varnished aluminum with minimal visual impact and is 360° completely adjustable. It is available in 3 different optics and has an LED (COB) CRI >90, 3000K (2700K/4000K light source on request) fed in direct current with incorporated convertor located inside the track adaptor.



## TECHNICAL DATA

<b>Wattage / Input</b>	12W
<b>Track Power Supply</b>	Remote 48VDC power supply for track, not included. See 48V Track datasheet
<b>Track Head</b>	Integral 48V LED Converter in Track Adapter
<b>Dimming</b>	Non-Dim, 0-10V Dim, Dali
<b>Construction</b>	Body: Aluminum
<b>CCT</b>	3000K (2700K, 4000K on request)
<b>CRI</b>	>90
<b>Delivered Lumens</b>	1550 lm (3000K)
<b>Efficacy</b>	129.2 lm/W (3000K)
<b>Optics</b>	24° standard (12°, 38° on request)
<b>Finishes</b>	White, Black
<b>Fixture Dimensions</b>	Head: Ø2.4" x 3.4" Base: 0.8" x 6.5"
<b>Fixture Weight</b>	1.76 lbs
<b>IP Rating</b>	IP40

Fixture Dimensions



## ORDERING INFORMATION

Example: BUT048L00005B13830110.US. Track ordered separately.

BUT048L00005					0	US
Model No.	Finish	Optic	CCT	Dimmability		
BUT048L00005	W1 - White B1 - Black	12 - 12° 24 - 24° 38 - 38°	27 - 2700K 30 - 3000K 40 - 4000K	ND - Non Dimmable 11 - 0-10V Dimming DA - DALI	0	US










Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES


48VDC - See Track Datasheets

### 48V TRACKS


<p><b>B55</b></p>   <p>See B55 Track datasheet for ordering code and power supply</p> 	<p><b>B30</b></p>   <p>See B30 Track datasheet for ordering code and power supply</p> 	<p><b>B-INSIDE</b></p>   <p>See B-Inside Track datasheet for ordering code and power supply</p> 
--	---	---

### PHOTOMETRIC DATA

Note: All photometry is 3000K



PHOTOMETRIC FILENAME : Q1 48V 24° - BUT048L00005B12430ND.IES



PHOTOMETRIC FILENAME : Q1 48V 24° - BUT048L00005B12430ND.IES

Job Name/Date:

Fixture Type Designation: