


# RDP DOWNLIGHT

The RDP Downlight is a vandal resistant, IP65 wet label downlight with a closed bottom and a clear polycarbonate bottom lens. It is offered in 4 color temperatures, 2 optics options and 5 standard finishes as well as 4 marine grade finishes. B.A.B.A. Compliant.



**MADE IN THE U.S.A.**

Fixture Dimensions - See page 2  
Concrete Drawing - See page 3



## TECHNICAL DATA

<b>Wattage / Input</b>	30W (120-277VAC or 347VAC)
<b>Power Supply</b>	Integral (0-10V Dimming)
<b>Construction</b>	Body: 18 Ga. Zinc Coated Steel Trim Ring: Die-cast Low Copper Alloy Lens: 3/16" Clear Polycarbonate
<b>CCT</b>	2700K, 3000K, 3500K, 4000K
<b>CRI</b>	>80
<b>Delivered Lumens</b>	2612 lm (3000K, 25°)
<b>Efficacy</b>	50.6 lm/W
<b>Optics</b>	25°, 45°
<b>Finishes</b>	5 Standard plus 4 Marine Grade (see below)
<b>Fixture Dimensions</b>	Ø7.16" x 9.82" x 11.48"
<b>Cut-Out Dimensions</b>	Ø8.5"
<b>Fixture Weight</b>	9.2 lbs
<b>LED Source</b>	Xicato XTM LED Module
<b>Color Consistency</b>	1x2 MacAdam Ellipse (1x2 SDCM)
<b>IP Rating</b>	IP65

## ORDERING INFORMATION

*Example: RDP-3030-V-1-W-25-C-11-0. Accessories ordered separately.*

RDP-BABA	-	-	1	-	W	-	-	-	-
Model #	CCT	Body	Lens	Cone	Optics	Driver	Finish	Options	
RDP-BABA	3027 - 27K	4 - Fully	1 - Standard	W - White	25 - 25°	C - 120-277VAC	11 - White Suede	0 - None	
(clear poly	3030 - 30K	Recessed			45 - 45°	w/ 0-10V	02 - Black Suede	1 - Emergency	
lens with	3035 - 35K	w/ Hanger				Dimming	18 - Tex. Bronze	Ballast	
opal center)	3040 - 40K	Bar Brackets				2 - 347VAC	TS - Silver	8 - Special	
		V - Fully				w/ 0-10V	<i>Add prefix "M" to</i>	Screws	
		Recessed				Dimming	<i>above colors for Marine</i>		
		for concrete					<i>Grade Clear Overcoat</i>		
		pour					PN - Polished		
							Nickel		
							<i>Marine Grade Clear</i>		
							<i>Overcoat NOT available</i>		
							<i>on Polished Nickel</i>		

Lower lumen packages are available.  
Contact Factory for information.


Job Name/Date:

Fixture Type Designation:

## PHOTOMETRIC DATA


Note all Photometry is 3000K

Maximum Candela = 12135




PHOTOMETRIC FILENAME : RDP30351W25CW0.IES

Maximum Candela = 5169



PHOTOMETRIC FILENAME : RDP30351W45CW0.IES


## DRAWING - See page 3 for Concrete drawing



Job Name/Date:

Fixture Type Designation:

## CONCRETE DRAWING



Job Name/Date:

Fixture Type Designation: