


Technical features



Available on request




101403P

RING MAXI







Designed by
NAVA + AROSIO

Floodlight for outdoor installation on a façade/wall, with 355° swivel base and allowing horizontal adjustment of +90° / -40°. Phospho-chromatized and polyester powder coated die-cast copper-free aluminum base and head, tempered safety glass, molded silicone gaskets and o-rings, with screws in stainless steel. Swivel joint with graduated scale and mechanical aiming lock. Built-in LED driver, with 1 COB CREE "CXB 2540" LED. IP66 rating.



Technical data

Wattage	42 WATT
IP Rating	IP66
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	1 COB CREE "CXB 2540" LED
Screws	Stainless steel
Transformer	Electronic power supply 120V 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M16 rubber grommet
Power cable	3.28' power cable included
Gross weight	8.82 lbs

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
cob led	 14°	4.950	117.85
cob led	 35°	4.752	113.14
cob led	 55°	4.560	108.57
4000°K neutral-white			
cob led	 14°	5.265	125.36
cob led	 35°	5.000	119.05
cob led	 55°	4.770	113.57

2700°K CCT available on request

Finish color options:



OTHER VIEW




OPTIONAL

AC044
SPIKE

AC050
HONEYCOMB
LOUVER

AC038
TREE STRAP
FOR RING SERIES


AC047
ANTI-GLARE
VISOR




OPTIONAL LIGHT DISTRIBUTIONS

These optional light distributions are obtained with special glass diffusers, product must be ordered as per light distribution requirement and these optics are not interchangeable

ELLIPTICAL



PRISMATIC



OPTIONAL

LUMINAIRE SUITABLE FOR POLE MOUNTING
IN SINGLE OR MULTIPLE COMBINATIONS

AC085 - POLE PLATE

Pole plate for pole mounting of all Ring models, suitable to be used with poles diam. min 3.0" and diam. max 4.7". Can be positioned on various staggered levels or on a single level, with the same pole. Made in phospho-chromatized and polyester powder coated die-cast copper-free aluminum material, molded silicone gaskets and screws in stainless steel.



AC088 - TREE-BRANCH BRACKET

Special bracket for Ring Maxi pole mounting, suitable to be used with poles diam. min 3.0" and diam. max 4.7". Can be positioned on various staggered levels or on a single level, with the same pole. Made in phospho-chromatized and polyester powder coated die-cast copper-free aluminum material, molded silicone gaskets and screws in stainless steel.

