

# RING MAXI RGBW

The Ring Maxi RGBW is an outdoor LED floodlight suitable for installation on a façade/wall, with 355° swivel base and horizontal adjustment of +90° / -40°. It has 3 standard finishes and 3 optics options.




Base Plate Included with Fixture

## TECHNICAL DATA

<b>Wattage / Input</b>	28W (24VDC)
<b>Power Supply</b>	Remote with DMX driver integrated See page 2 for remote power supplies
<b>Construction</b>	Body: Die-Cast Copper-Free Aluminum Screws: Stainless Steel Lens: Tempered, Safety Glass Cable Length: 3.28" included
<b>CCT</b>	RGBW - DMX Control Built Into Fixture
<b>CRI</b>	>80
<b>Lumen Output</b>	992 lm (25°)
<b>Efficacy</b>	35.4 lm/W (25°)
<b>Optics</b>	3 Standard (see below)
<b>Finishes</b>	3 Standard, Custom RAL (see below)
<b>Fixture Dimensions</b>	Ø5.71" x 7.32" w x 10.91" h
<b>Fixture Weight</b>	8.82 lbs
<b>LED Source</b>	6 CREE "XML" RGBW LED
<b>IP Rating</b>	IP66
<b>Impact Rating</b>	IK10

Fixture Dimensions



## ORDERING INFORMATION

Example: 101406RGBWP-12-TG. Power Supplies / Accessories ordered separately.

101406RGBWP	-		-	
Model No.	Optics	Finish		
101406RGBWP	12 - 12° 25 - 25° 35 - 35°	TG - Textured Grey (RAL 9006) AG - Anthracite Grey (RAL 7016) MB - Matte Black (on request)		

Job Name/Date:

Fixture Type Designation:


## ACCESSORIES

Installation

Anti-Glare



**AC044**  
Ground Spike



**AC050**  
Honeycomb Louver



**AC038**  
Tree Strap  
for Ring Series




**AC047**  
Anti-glare visor

## ACCESSORIES - Optional



**AC085**  
Pole Plate



**AC088**  
Tree Branch  
Bracket

## SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00543</a>	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-2

For other power supply options consult factory.

## PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation: