RING MEGA COB




datasheet





Base Plate Included with Fixture

Fixture Dimensions



series, suitable for installation on a façade/wall, with 355° swivel base and horizontal adjustment of $+90^{\circ}$ / -40° . It has 3 standard finishes and 3 optics options.

The Ring Mega COB is an outdoor LED floodlight, and largest of the Ring

TECHNICAL DATA

TEGINIOAE DAIA				
Wattage	75W			
Power Supply	Integral 120-277			
Construction	Body: Die-Cast Copper-Free Aluminum			
	Screws: Stainless Steel			
	Lens: Tempered, Safety Glass			
	Cable Length: 3.28" included			
ССТ	3000K, 4000K			
CRI	>80			
Lumen Output	10,100 lm (3000K, 20°)			
Efficacy	123.2 lm/W (3000K, 20°)			
Optics	20°, 40°			
Finishes	3 Standard, Custom RAL (see below)			
Fixture Dimensions	Ø7.64" x 9.61" w x 14.88" h			
Fixture Weight	17.6 lbs			
LED Source	1 x CREE "CXB 3590" LED			
IP Rating	IP66			
Impact Rating	IK10			

ORDERING INFORMATION

Example: 101407P-30K-20-TG. Accessories ordered separately.

101407P	-	-	-
Model No.	ССТ	Optics	Finish
101407P	30K - 3000K 40K - 4000K	20 - 20° 40 - 40°	TG - Textured Grey (RAL 9006) AG - Anthracite Grey (RAL 7016) MB - Matte Black (on request)

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

1 of 2

datasheet

ACCESSORIES

Installation



Anti-Glare



AC086 Anti-Glare Visor




AC087 Honeycomb Louver

ACCESSORIES - Optional



AC085 Pole Plate







AC089 Tree Branch Bracket

PHOTOMETRIC DATA

Note: all photometry is 3000K



Job Name/Date:



PHOTOMETRIC FILENAME : RING MEGA COB 30K 40° - 101407P.IES

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

2 of 2