


Slice C is an indoor ceiling mounted luminaire with a minimal design made of a white painted aluminum body and AirCoral® front panel that maintains all the features of its totally disappearing recessed version, Slice. It is available in 3 color temperatures and diffused optics.



## TECHNICAL DATA


<b>Wattage / Input</b>	8.5W (350mA)
<b>Power Supply</b>	Remote, not included. See page 2.
<b>Construction</b>	Body: AirCoral®
<b>CCT</b>	3000K (2700K, 4000K on request)
<b>CRI</b>	>90
<b>Delivered Lumens</b>	612 lm (3000K)
<b>Efficacy</b>	72 lm/W
<b>Optics</b>	Diffuse
<b>Finishes</b>	AirCoral®
<b>LED Source</b>	COB professional LED
<b>Fixture Dimensions</b>	5.91" l x 5.91" w x 2.36" h
<b>Aperature</b>	2.36" x 2.36"
<b>Fixture Weight</b>	—
<b>IP Rating</b>	IP40

The body is made of Aircoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for Aircoral® calculator.

Additionally, Aircoral® is:

- Antibacterial.
- Antifungal.
- Scratch-resistant.
- Dust-resistant.
- Suitable for painting.
- LEED recognized material.

Fixture Dimensions



## ORDERING INFORMATION

Example: BU1922.AC4S00M30.ND.US.

BU1922.AC4S00M		ND.US
<b>Model No.</b>	<b>CCT</b>	
BU1922.AC4S00M	27 - 2700K	ND.US
	30 - 3000K	
	40 - 4000K	

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

350mA

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00466-P</a>	0-10V Dimming to 1.0%	120-277VAC to 350mA, 10W, Class 2	1-1
<a href="#">PPLT00496</a>	Phase Dim (120V only)	120VAC to 350mA, 12W, Class 2	1-1
<a href="#">PPLT00263</a>	Leading / Trailing-Edge Dimming to 10% (120V only)	120-277VAC to 350mA, 32W, Class 2	1-1
<a href="#">PPLT00467-P</a>	0-10V Dimming to 1.0%	120-277VAC to 350mA, 50W, Class 2	1-2
<a href="#">PPLT00561-P</a>	0-10V Dimming to 0.1%	120-277VAC to 350mA, 100W, Class 2	1-2

## Suggested Lutron Compatible


Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
<a href="#">PPLT00516</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 13W, Class 2	1-1
<a href="#">PPLT00179</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 19W, Class 2	2-2

For other power supply options consult factory.

## PHOTOMETRIC DATA

All photometry is 3000K

Maximum Candela = 217.1



PHOTOMETRIC FILENAME : SLICE C - BU1922.AC.IES

Job Name/Date:

Fixture Type Designation: