


Spike Mega is an IP66-rated luminaire suitable for installation as a bollard, that comes with 180° or 360° diffused light emission and has a higher wattage than its counterpart, Spike. It is available in 2 color temperatures and diffused optics.



TECHNICAL DATA

Wattage / Input	13.2W - 180° Emission 26.4W - 360° Emission
Power Supply	Remote, not included. Consult Factory.
Construction	Head: Aluminum (Anodized to 18 microns) Pole: Stainless Steel Lens: Satin PMMA Cable Length: 3.28'
CCT	3000K, 4000K
BUG Rating	B0-U3-G1 (180°) B1-U3-G2 (360°)
Delivered Lumens	1701 lm (180° - 3000K) 3402 lm (360° - 3000K)
Efficacy	128.8 lm/W (3000K)
Optics	Diffused 180° or 360°
Finishes	5 Standard, See Below
Fixture Dimensions	Head: Ø7.87" x 0.79" h Pole Height: 118.11" h
Color Consistency	<3-Step MacAdam
IP Rating	IP66
Impact Resistance	IK08

Fixture Dimensions



See Page 2 for Pole Accessories

ORDERING INFORMATION

Example: LM05.104365.US.03.DI.BP.00. Accessories / Power Supplies ordered separately.

		DI		00
Model No.	Finish	Optics	CCT	Driver
LM05.104365.US - 180°	01 - White	DI - Diffused	BP - 3000K	00 - Remote
LM05.104366.US - 360°	02 - Black		BF - 4000K	(see page 2)
	03 - Aluminum			
	04 - Cor-ten			
	11 - Anthracite			


Job Name/Date:

Fixture Type Designation:


SUGGESTED POWER SUPPLIES

Consult Factory

ACCESSORIES - Installation




Anchor Plate
LM20.101235 (Ø7.87" x 11.81" h)




PHOTOMETRIC DATA

Note: All photometric data is 3000K



PHOTOMETRIC FILENAME : SPIKE MEGA 180° 30K LM05.104365.XX.XXX.DI.XX.IES



PHOTOMETRIC FILENAME : SPIKE MEGA 360° 30K LM05.104366.XX.XXX.DI.XX.LDT

Job Name/Date:

Fixture Type Designation: