





datasheet


Spritz is a rechargeable table luminaire resistant to the elements and with high performance construction materials. It is made up of an aluminum head and steel stem whose base is magnetic, which connects with force to a metal surface or plate. It is available in 3000K with 3 level touch dimming and 6 standard finishes.

TECHNICAL DATA

Wattage	2.9W			
Power Supply	Integral - Rechargable using Power Cord			
	Battery Autonomy >7 hours (device on full			
	performance) and >10 hours (on first			
	dimmable level of luminaire)			
Construction	Head: Aluminum			
	Stem: Steel (battery inside stem)			
	Lens: Satin Acrylic (PMMA)			
Dimming	Touch Dimming to 3 Levels - Integral			
CCT	3000K			
BUG Rating	B0-U3-G0			
Delivered Lumens	360 lm (3000K)			
Efficacy	124.1 lm/W			
Optics	Diffuse			
Finishes	6 Standard, See Below			
Fixture Dimensions	Head: 3.54" x 3.54" x 0.79" h			
	Stem: 1.18" x 1.18" x 14.33" h			
	Metal Base: 4.72" x 4.72" x 0.08" h			
Color Consistency	<3-Step MacAdam			
IP Rating	IP55			
Impact Resistance	IK07			



Fixture Dimensions



ORDERING INFORMATION Example: LM04.102694.US.04.BP.

		ВР
Model No.	Finish	ССТ
LM04.102390D.US - Single Version Kit (Luminaire, Metal Base, Battery Charger) LM04.102694.US - Separate Fixture (No Metal Base, Battery Charger)	01 - White02 - Black03 - Aluminum	BP - 3000K
Accessories (see more on page 2) LM20.102503.US - Metal Base (For the non-magnetic surface) LM04.102695.US - Mutiple Battery Charger (Up to 6 luminaires)	04 - Cor-ten05 - Satin Stainless11 - Anthracite	

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042










datasheet

SEPARATE COMPONENTS





LM20.102503 Metal Base




LM20.102695.US Multiple Battery Charger (up to 6 luminaires) 15.75" x 11.81" x 1.38" h





PHOTOMETRIC DATA

Note: All photometric data is 3000K



PHOTOMETRIC FILENAME : SPRITZ SINGLE LM04.102390.XX.XX.IES

Job Name/Date:

Fixture Type Designation: