


Stripp XF is a recessed long and narrow fixture made of CALCYT® plaster that can be used as an up- or downlight and is equipped with state of the art LED technology. It is available in 5 color temperatures and can be directly installed in solid walls as well as in gypsum walls by means of an optional plasterkit.

TECHNICAL DATA

Wattage / Input	1W (350mA)
Power Supply	Remote, not included. See page 2.
Construction	Body: CALCYT® Plaster
CCT	2200K, 2700K, 3000K, 4000K, Royal Blue
CRI	>90, >80
Optics	Fixed
Finishes	CALCYT® Plaster - fully paintable
Fixture Dimensions	3.07" w x 21.46" h x 2.36" l
Cut-out Dimension	3.27" x 21.65"
Aperature	0.67" w x 16.26" h
Color Consistency	3-Step MacAdam
IP Rating	IP20, IP54



Ceiling Cut-Out: 3.27" x 21.65"
Fixture Dimensions



ORDERING INFORMATION

Example: 141 60 100. Accessories / Power Supplies ordered separately.

Model No.	Description
141 60 500 - 2200K	1W, 100 lm, CRI 80, IP20 Indoor
141 60 000 - 2700K	1W, 100 lm, CRI 90, IP20 Indoor
141 60 100 - 3000K	1W, 100 lm, CRI 90, IP20 Indoor
141 60 200 - 4000K	1W, 100 lm, CRI 90, IP20 Indoor
141 60 300 - royal blue	1W, 100 lm, CRI 90, IP20 Indoor
141 60 501 - 2200K	1W, 100 lm, CRI 80, IP54 Bathroom
141 60 001 - 2700K	1W, 100 lm, CRI 90, IP54 Bathroom
141 60 101 - 3000K	1W, 100 lm, CRI 90, IP54 Bathroom
141 60 201 - 4000K	1W, 100 lm, CRI 90, IP54 Bathroom
141 60 301 - royal blue	1W, 100 lm, CRI 90, IP54 Bathroom
141 60 505 - 2200K	1W, 100 lm, CRI 80, IP54 Outdoor
141 60 005 - 2700K	1W, 100 lm, CRI 90, IP54 Outdoor
141 60 105 - 3000K	1W, 100 lm, CRI 90, IP54 Outdoor
141 60 205 - 4000K	1W, 100 lm, CRI 90, IP54 Outdoor
141 60 305 - royal blue	1W, 100 lm, CRI 90, IP54 Outdoor

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

350mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00138	0-10V Dimming to 10%	120-277VAC to 350mA, 4W, Class 2	2-3
PPLT00496	Phase Dim (120V only)	120VAC to 350mA, 12W, Class 2	3-9
PPLT00480-P	0-10V Dimming to 1.0%	120-277VAC to 350mA, 30W, Class 2	1-16
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 50W, Class 2	1-16
PPLT00538-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 100W, Class 2	1-68

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00247	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 7W, Class 2	4-5
PPLT00516	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 13W, Class 2	6-11
PPLT00179	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 19W, Class 2	12-16

For other power supply options consult factory.

ACCESSORIES - Installation

743 01 000

Outer Casing

Housing: perforated aluminum

Job Name/Date:

Fixture Type Designation: