

# STRIPP XL IP20

Stripp XT IP20 is an indoor recessed long and narrow fixture made of CALCYT® plaster that can be used as an up- or downlight and is equipped with state of the art LED technology. It is available in 5 color temperatures and can be directly installed in solid walls as well as in gypsum walls by means of an optional plasterkit.



Ceiling Cut-Out: 3.27" x 21.65"  
Fixture Dimensions

## TECHNICAL DATA

<b>Wattage / Input</b>	1W, 2W, 4W (350mA)
<b>Power Supply</b>	Remote, not included. See page 2.
<b>Construction</b>	Body: CALCYT® Plaster
<b>CCT</b>	2200K, 2700K, 3000K, 4000K, Royal Blue
<b>CRI</b>	>90, >80
<b>Optics</b>	Fixed
<b>Finishes</b>	CALCYT® Plaster - fully paintable
<b>Fixture Dimensions</b>	3.07" w x 21.46" h x 2.36" l
<b>Cut-out Dimension</b>	3.27" x 21.65"
<b>Aperature</b>	1.54" w x 16.34" h
<b>Color Consistency</b>	3-Step MacAdam
<b>IP Rating</b>	IP20

## ORDERING INFORMATION

Example: 143 62 100. Accessories / Power Supplies ordered separately.

Model No.	Description
143 60 500 - 2200K	1W, 100 lm, CRI 80, IP20 Indoor
143 60 000 - 2700K	1W, 100 lm, CRI 90, IP20 Indoor
143 60 100 - 3000K	1W, 100 lm, CRI 90, IP20 Indoor
143 60 200 - 4000K	1W, 100 lm, CRI 90, IP20 Indoor
143 60 300 - royal blue	1W, 100 lm, CRI 90, IP20 Indoor
143 62 500 - 2200K	2W, 200 lm, CRI 80, IP20 Indoor
143 62 000 - 2700K	2W, 200 lm, CRI 90, IP20 Indoor
143 62 100 - 3000K	2W, 200 lm, CRI 90, IP20 Indoor
143 62 200 - 4000K	2W, 200 lm, CRI 90, IP20 Indoor
143 62 300 - royal blue	2W, 200 lm, CRI 90, IP20 Indoor
143 61 500 - 2200K	4W, 400 lm, CRI 80, IP20 Indoor
143 61 000 - 2700K	4W, 400 lm, CRI 90, IP20 Indoor
143 61 100 - 3000K	4W, 400 lm, CRI 90, IP20 Indoor
143 61 200 - 4000K	4W, 400 lm, CRI 90, IP20 Indoor
143 61 300 - royal blue	4W, 400 lm, CRI 90, IP20 Indoor



Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

350mA

Part Number	Description	Input/Output	# of Fixtures		
			1W	2W	4W
<a href="#">PPLT00138</a>	0-10V Dimming to 10%	120-277VAC to 350mA, 4W, Class 2	2-3	1-1	N/A
<a href="#">PPLT00496</a>	Phase Dim (120V only)	120VAC to 350mA, 12W, Class 2	3-9	2-6	1-3
<a href="#">PPLT00480-P</a>	0-10V Dimming to 1.0%	120-277VAC to 350mA, 30W, Class 2	1-16	1-9	1-4
<a href="#">PPLT00309-P</a>	0-10V Dimming to 0.1%	120-277VAC to 350mA, 50W, Class 2	1-16	1-9	1-4
<a href="#">PPLT00538-P</a>	0-10V Dimming to 0.1%	120-277VAC to 350mA, 100W, Class 2	1-68	1-40	1-16

## Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures		
						1W	2W	4W
<a href="#">PPLT00247</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 7W, Class 2	4-5	2-3	1-1
<a href="#">PPLT00516</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 13W, Class 2	6-11	3-6	2-3
<a href="#">PPLT00179</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 19W, Class 2	12-16	6-9	3-4

For other power supply options consult factory.

## REQUIRED ACCESSORIES - Installation

743 01 000

Outer Casing

Housing: perforated aluminum

Job Name/Date:

Fixture Type Designation: