



Tetris is a trimless multiple 3-cell adjustable downlight. Made of AirCoral®, this fixture is installed in plasterboard ceilings and seamlessly integrates into the landscape making it perfect for a variety of architectural projects. Available in 3000K as standard with 40° optics.



TECHNICAL DATA

Wattage / Input	3 x 9W (500mA)
Power Supply	Remote, not included. See page 2.
Construction	Body: AirCoral®
CCT	3000K (2700K, 4000K on request, consult factory)
CRI	>90
Delivered Lumens	780 lm (3000K)
Efficacy	105 lm/W (3000K)
Optics	40°
Fixture Dimensions	14.96" l x 5.91" w x 5.12" h
Aperture	12.60" x 3.54"
Cut Out Dimensions	15.35" x 6.30"
Fixture Weight	5.95 lbs
LED Source	1 COB Professional LED
IP Rating	IP20

Fixture Dimensions:



The body is made of Aircoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for Aircoral® calculator.

Additionally, Aircoral® is:

- Antibacterial.
- Antifungal.
- Scratch-resistant.
- Dust-resistant.
- Suitable for painting.
- LEED recognized material.

ORDERING INFORMATION

Example: BU6246.Z.AC.US 30 WD. Power Supplies ordered separately.

BU6246.Z		AC	.US
Model No.	CCT	Finish	
BU6246.Z	30 WD - 3000K (standard) 27 WD - 2700K (on request) 40 WD - 4000K (on request)	AC - AirCoral®	.US

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

500mA


Part Number	Description	Input/Output	Fixtures
PPLT00480-P	0-10V Dimming to 1.0%	120-277VAC to 500mA, 30W, Class 2	1-1
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 500mA, 50W, Class 2	1-1

For other power supply options consult factory.

PHOTOMETRIC DATA

Note: All photometry is 3000K

Maximum Candela = 1939



Job Name/Date:

Fixture Type Designation: