



The Underline Series is a walkover luminaire made of DurCoral® a material three times stronger than concrete and perfect for exterior environments. It is meant to sit flush with other tiles, pavers, or other flooring materials as well as within grassy areas.



Fixture Dimensions
19.69" l x 19.69" w x 1.57" total height
(tile is 0.79"h)



TECHNICAL DATA

Wattage / Input	5.5W (24VDC)
Power Supply	Remote, not included. See page 2.
Construction	Body: DurCoral®
CCT	3000K
CRI	>90
LED Lumens	220 lm (3000K)
Efficacy	40 lm/W
Optics	120°
Finishes	Unfinished
Aperture	15.75" x 0.59"
Fixture Dimensions	19.69" l x 19.69" w x 1.57" h (tile is 0.79" h)
Fixture Weight	24.25 lbs
IP Rating	IP68
Impact Rating	-

The body is made of DurCoral®, a high-performance "hi-tech" material born from the union of Coral® and cement. It is an aggregate twice as hard as concrete, which allows very high performances in terms of quality, flow and resistance and that, above all, differs from other outdoor materials, for the possibility of being treated with any type of paint and finish. Distinguished by the ability to resist abrasion, insensitive to ultraviolet rays, pollution and atmospheric agents is certainly the ideal material to be placed outdoors.

ORDERING INFORMATION

Example: BU1741.DC.US. Power Supplies ordered separately.

BU1741.DC.US

Model No.

BU1741.DC.US

Product Code:

Job Name/Date:

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00284	Non-Dim	120-277VAC to 24VDC, 100W, Class 2	1-14
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	2-14

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00530	L3D0E / L3D03W	L3D0	100%-0.1%	Hi-Lume™ 1% EcoSystem™ / 3-Wire Fade to Black LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-14

DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures 5.5W
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-13

For other power supply options consult factory.

Product Code:

Job Name/Date: