


A totally recessed fixture made of AirCoral®, Unleaf is installable on plasterboard or brick walls and ceilings. The product surface sinks into the wall and offers a wide beam light distribution.



Ceiling Cut-Out: 18.1" x 18.1"

Fixture Dimensions:



TECHNICAL DATA

| | |
|---------------------------|-----------------------------------------------------|
| Wattage / Input | 2 x 6.5W (350mA) |
| Power Supply | Remote, not included. See page 2. |
| Construction | Body: AirCoral® |
| CCT | 3000K (2700K, 4000K on request, consult factory) |
| CRI | >90 |
| Delivered Lumens | 315 lm per beam (3000K) |
| Efficacy | 48 lm/W (3000K) |
| Optics | 120° wide beam |
| Finishes | Unfinished |
| Cut-Out Dimensions | 18.1" x 18.1" |
| Fixture Dimensions | 17.72" l x 17.72" w x 12.40" |
| Fixture Weight | 22.93 lbs |
| IP Rating | IP20 |

The body is made of Aircoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for Aircoral® calculator.

Additionally, Aircoral® is:

- Antibacterial.
- Antifungal.
- Scratch-resistant.
- Dust-resistant.
- Suitable for painting.
- LEED recognized material.

ORDERING INFORMATION

Example: BU2998.30.AC.US. Power Supplies ordered separately.

| | |
|--------------------------------------------------------------------------|-------------------------|
| BU2998. | AC.US |
| Model No. BU2998 (3000K standard) (2700K, 4000K on request) | AC.US - AirCoral |

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

350mA

| Part Number | Description | Input/Output | Fixtures |
|-----------------------------|----------------------------------------------------|------------------------------------|----------|
| PPLT00468 | Phase Dim (120V Only) | 120VAC to 350mA 14W, Class 2 | 1-2 |
| PPLT00480-P | 0-10V Dimming to 1.0% | 120-277VAC to 350mA, 30W, Class 2 | 1-3 |
| PPLT00263 | Leading / Trailing-Edge Dimming to 10% (120V only) | 120-277VAC to 350mA, 32W, Class 2 | 2-2 |
| PPLT00309-P | 0-10V Dimming to 0.1% | 120-277VAC to 350mA, 50W, Class 2 | 1-3 |
| PPLT00538-P | 0-10V Dimming to 0.1% | 120-277VAC to 350mA, 100W, Class 2 | 1-12 |

Suggested Lutron Compatible Drivers


| Part Number | Option | Lutron SKU | Dim Range | Description | Input/Output | Fixtures |
|---------------------------|----------------|------------|-----------|------------------------------------------------|-----------------|----------|
| PPLT00247 | L3DAE / L3DA3W | L3DA | 100%-1% | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC, 7W | 1-1 |
| PPLT00516 | L3DAE / L3DA3W | L3DA | 100%-1% | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC, 13W | 1-2 |
| PPLT00179 | L3DAE / L3DA3W | L3DA | 100%-1% | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC, 19W | 2-2 |

For other power supply options consult factory.

PHOTOMETRIC DATA

All photometry is 3000K

Maximum Candela = 84.6



PHOTOMETRIC FILENAME : UNLEAF - BU2998.IES

Job Name/Date:

Fixture Type Designation: