

Dotz Ursa Major is a sleek 1.9" round wet label LED downlight with on board 0-10V dimming which can be installed recessed with 3 springs or panel mounted with 1.0" conduit nut on the threaded part of the body. It comes with frosted solid Acrylume™ acrylic trim.



## MADE IN THE USA

Complies with LM79 and LM80  
Complies with ARRA

Fixture Dimensions  
See Drawing on page 2.

## TECHNICAL DATA

<b>Wattage / Input</b>	1W, 3W (24VDC)
<b>Power Supply</b>	Remote, not included. See page 2.
<b>Construction</b>	Body: Die Cast Aluminum Lens: 3/16" Tempered Glass Cable Length: 2.0'
<b>CCT</b>	3000K, 4000K, 5000K (Static color on request)
<b>CRI</b>	>80
<b>Delivered Lumens</b>	192 lm (3W, 3000K)
<b>Efficacy</b>	64 lm/W (3W, 5000K)
<b>Optics</b>	None
<b>Finishes</b>	Frosted Acrylic (Acrylume™)
<b>LED Source</b>	3W CREE LED
<b>Fixture Dimensions</b>	Ø1.89" x 4.56" I
<b>Body</b>	Ø1.16"
<b>Cut-out Dimension</b>	Ø1.25"
<b>IP Rating</b>	IP65, Weatherproof Gland

## ORDERING INFORMATION


**Example: URA-3-30-0-FA. Power Supplies ordered separately.**

URA	-		-		-	0	-	0	-	FA
Model No.	Wattage	CCT	Lens	Optics	Finish					
URA - Ursa Major	1 - 1W 3 - 3W	30 - 3000K 40 - 4000K 50 - 5000K Note: Static Red, Green, Blue, Amber on request.	0 - None	0 - None	FA - Frosted Acrylic					

Job Name/Date:

Fixture Type Designation:

## FIXTURE DIMENSIONS



## SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures	
			1W	3W
<a href="#">PPLT00155</a>	Non-Dim	120-277VAC to 350mA, 30W, Class 2	1-24	1-8
<a href="#">PPLT00158</a>	Non-Dim	120-277VAC to 350mA, 100W, Class 2	1-80	1-26

## Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures	
						1W	3W
<a href="#">PPLT00530</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-76	1-25

For other power supply options consult factory.


Job Name/Date:

Fixture Type Designation:

## PHOTOMETRIC DATA

Dotz Round 3W 5000K Clear Lens - No Optic


Maximum Candela = 895



LTL TEST #21284

CIRCLE-OF-LIGHT

Ft below	FC nadir	Dia @ 50%
6.0	24.9	1.4
8.0	14.0	1.9
10.0	8.9	2.4
12.0	6.2	2.9
14.0	4.6	3.3
16.0	3.5	3.8



NOTE: 'Dia' spans the edge-points that are half of nadir FC

FILENAME : DOTZ 1X3W 5000K ROUND CLEAR LENS NARROW OPTIC LTL21284.IES

Job Name/Date:

Fixture Type Designation: