



datasheet





**Fixture Dimensions** 



## TECHNICAL DATA

ant for output below 80°.

Wattage / Input	18W	
Power Supply	Integral	
Construction	Body: DurCoral®	
	Lens: Satin White Glass (1/2" thick)	
ССТ	3000K (2700K on request)	
CRI	>85	
BUG Rating	B0-U0-G0	
Delivered Lumens	1602 lm (3000K)	
	Dark Sky compliant, output below 80°	
Efficacy	89 lm/W	
Optics	120°	
Finishes	DurCoral <sup>®</sup>	
Fixture Dimensions	9.84" I x 9.84" w x 6.77" h	
Aperature	8.86" x 8.86"	
Fixture Weight	16.53 lbs	

Valo IP65 is a floor lighting device for indoor or outdoor use made of DurCoral® that is perfect for highlighting spaces, furniture and architecture or enhancing terraces, walkways and gardens. It is available in 3000K as standard with a 120° optic and an IP65 protection rating. Dark Sky compli-

The body is made of DurCoral®, a high-performance "hi-tech" material born from the union of Coral® and cement. It is an aggregate twice as hard as concrete, which allows very high performances in terms of quality, flow and resistance and that, above all, differs from other outdoor materials, for the possibility of being treated with any type of paint and finish. Distinguished by the ability to resist abrasion, insensitive to ultraviolet rays, pollution and atmospheric agents is certainly the ideal material to be placed outdoors.

## PHOTOMETRIC DATA

Note all Photometry is 3000K

Maximum Candela = 250.5
- C0 - C180 - C90 - C270
125

Fixture Type Designation:

## ORDERING INFORMATION

Example: BU1624.DC.US. Power Supplies ordered separately.

BU1624	DC	US
Model No.	Finish	
BU1624	DC - DurCoral®	US

Job Name/Date:

P: 908-996-7710 F: 908-996-7042

1 of 1