

interior walls.





datasheet





Wall Cut-Out: 27.44" x 11.38" Fixture Dimensions





TECHNICAL DATA

Wattage / Input	15.9W (350mA)
Power Supply	Remote, not included. See page 2.
Construction	Body: CALCYT® Plaster Lens: Clear Acrylic
ССТ	2700K, 3000K
CRI	>80
Optics	Fixed
Finishes	Paintable Plaster
Cut-Out Dimensions	27.48" x 11.42"
Fixture Dimensions	27.28" l x 2.76" w x 11.22" h
LED Source	2000 lm LED
Color Consistency	4-Step MacAdam
IP Rating	IP20

Wave is a recessed wall fixture that is made of CALCYT® plaster that blends effortlessly into traditional and contemporary interiors. It is available in 2 color temperatures and features paintable plaster to easily match your

ORDERING INFORMATION

Example: 316 04 100. Accessories / Power Supplies ordered separately.

Model No.	Description	
316 04 000 - 2700K	2000 lm LED - Remote Driver	
316 04 100 - 3000K	2000 Im LED - Remote Driver	

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

1 of 2





datasheet

SUGGESTED POWER SUPPLIES

350mA


Part Number	Description	Input/Output	# of Fixtures
PPLT00480-P	0-10V Dimming to 1.0%	120-277VAC to 350mA, 30W, Class 2	1-1
PPLT00309-P	0-10V Dimming to 0.1%	0-10V Dimming to 0.1% 120-277VAC to 350mA, 50W, Class 2	
PPLT00561-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 100W, Class 2	1-1

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00179	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA , 19W, Class 2	1-1

For other power supply options consult factory.


REQUIRED ACCESSORIES Installation



716 01 000Outer Casing

PHOTOMETRIC DATA

Note all Photometry is 3000K



Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042 2 of 2