



datasheet


XJR9 is a round recessed, adjustable ( $\pm 30$ ) luminaire for indoor installation on plasterboard walls or ceilings. It has a light source with adjustable visible mechanisms which creates beams that embellish the environment without invading it. It is available in a static white version (3000K standard) with a 40° wide beam and a white finish.

## **TECHNICAL DATA**

Wattage / Input	9W (500mA) Static White		
Power Supply	Remote, not included. See page 2.		
Construction	Body: Aluminum		
ССТ	3000K (2700K, 4000K on request)		
CRI	>90		
Delivered Lumens	557 lm (3000K)		
Efficacy	61.9 lm/W (3000K)		
Optics	40° Wide Beam		
Finishes	Matte White		
<b>Cut-Out Dimensions</b>	Ø2.95"		
Fixture Dimensions	Ø3.54" x 2.56"		
Aperature	Ø2.36"		
Fixture Weight	0.44 lbs		
LED Source	LED COB Professional		
IP Rating	IP20		



**Fixture Dimensions** 





## **ORDERING INFORMATION**

Example: BU1041 WH 2 R 40 M 30 WD.US. Power supplies for remote ordered separately.

BU1041	WH	2 R 40		.us
Model No.	Finish	Optics	CCT	
BU1041 - Static White	<b>WH</b> - white	<b>2 R 40</b> - 40°	M 30 WD - 3000K (standard) M 27 WD - 2700K (on request) M 40 WD - 4000K (on request)	.US

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

1 of 2





datasheet

## **SUGGESTED POWER SUPPLIES**


500mA - 9W Static White Version

Part Number	Description	Input/Output	Fixtures
PPLT00154	0-10V Dimming to 10%	120-277VAC to 500mA, 12W, Class 2	1-1
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 500mA 20W, Class 2	1-2
PPLT00527	Phase Dim (120V Only)	120VAC to 500mA, 25W, Class 2, IP66	2-2
PPLT00308-P	0-10V Dimming to 0.1%	120-277VAC to 500mA, 30W, Class 2	1-2
PPLT00168-P	0-10V Dimming to 1.0%	120-277VAC to 500mA, 50W, Class 2	1-4
PPLT00538-P	0-10V Dimming to 0.1%	120-277VAC to 500mA, 100W, Class 2	1-8

For other power supply options consult factory.

## **PHOTOMETRIC DATA**

All photometry is 3000K



Job Name/Date:

Fixture Type Designation: