Indoor 48V Light modules

Z1 48V











Frenchtown, NJ 08825

matte black painted

Z1 48V is a 48V track fitting characterised by a miniaturized projector with a diameter of only 0.9", completely directional on vertical and horizontal axes. Available in a standard white or black finish, Z1 48V is a product which guarantees high performances with a minimum visual impact. The Z1 48V projector has an LED (COB) CRI >90, 3000K (2700K/4000K light source on request) fed in direct current with incorporated convertor located inside the track adaptor.



www.designplan.com


Tel: (908) 996-7710 Fax: (908) 996-7042

3.0" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6" | 1.6

Ø0.9"



CODE COMPOSITION



example of code composition

BUT048 L 00003 W1 22 27 ND 0

TECHNICAL FEATURES

BUT048 L 00003 XX Code Projector \pm 360° / \pm 90° Туре ▲ ◀ 👙 🗼 White I Black Finishing 0.88 lbs Weight Mounting Track 48V IP rating IP40 Control gear Remote 48VDC - see track datasheet Lamp type **=**[] Lamp wattage 1 x 6W 520 lm - 3000K Luminous efficacy Beam 22° Light distribution Beam 50° (on request) White 3000K White 2700K | 4000K (on request) Light colour Voltage connection 48 VDC >90