

datasheet


Z1 48V is a miniature high performance projector for use with the 48V track system with a diameter of only 0.9", completely adjustable on vertical and horizontal axes. Z1 48V has an LED (COB) CRI >90, 3000K (2700K/4000K light source on request) fed in direct current with incorporated convertor located inside the track adaptor.

TECHNICAL DATA

Wattage / Input	6W			
wattage / iliput				
Track Power Supply	Remote 48VDC power supply for track,			
	not included. See 48V Track datasheet			
Track Head	Integral 48V LED Converter in Track Adapter			
Dimming	Non-Dim, 0-10V Dim, Dali			
Construction	Body: Aluminum			
ССТ	3000K (2700K, 4000K on request)			
CRI	>90			
Delivered Lumens	520 lm (3000K)			
Efficacy	86.7 lm/W (3000K)			
Optics	22° standard, 50° on request			
Finishes	White, Black			
Fixture Dimensions	Head: Ø0.9" x 3.0"			
	6.5" x 5.1"			
Fixture Weight	0.88 lbs			
IP Rating	IP40			



Fixture Dimensions



ORDERING INFORMATION

Example: BUT048L00003W12230110.US. Track ordered separately.

BUT048L00003					0	. US
Model No.	Finish	Optic	ССТ	Dimmability		
BUT048L00003	W1 - White B1 - Black	22 - 22° 50 - 50°	27 - 2700K 30 - 3000K 40 - 4000K	ND - Non Dimmable 11 - 0-10V Dimming DA - DALI	0	US

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042



datasheet

SUGGESTED POWER SUPPLIES


48VDC - See Track Datasheets

48V TRACKS

B55



See B55 Track datasheet for ordering code and power supply




48.0" or 96.0"



See B30 Track datasheet for ordering code and power supply





B30



B-INSIDE








3.94"

PHOTOMETRIC DATA

All photometry is 3000K



Job Name/Date:

Fixture Type Designation:

2 of 2