


Technical features



Technical data


Wattage	20 WATT
IP Rating	IP66
IK Rating	IK09
Material	High corrosion resistance extruded copper-free aluminum head and extruded pole
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	NR. 24 x CREE "XH-G" LED
Screws	Stainless steel
Transformer	Electronic power supply 120VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	PG11
Power cable	4.92' power cable included
Gross weight	9.48 lbs



602202P

ALDER 800

Designed by
NAVA + AROSIO

31.50" height bollard, for outdoor installation, 360° light distribution, phospho-chromatized and polyester powder coated die-cast aluminum head and extruded pole. Tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver 120VAC 50-60Hz, with 24 x CREE "XH-G" LED. IP66 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid-power led	 radial 360°	1,600	80.00
4000°K neutral-white			
mid-power led	 radial 360°	1,650	82.50

Finish color options:

-  Textured Grey RAL 9006
-  Anthracite Grey RAL 7016
-  Matte Black (on request)



AC065 ANCHORAGE UNIT FOR ALDER SERIES

