**Surface** 

3.94" Ø1.97" 3.94"

# **BARD**



## SEMI-RECESSED COMPLETELY PAINTABLE LIKE THE CEILING.

Bard is a semi-recessed luminaire installable on plasterboard ceilings, equipped with a Coral® body and a spring mechanism that allows the product to be fixed to the false ceiling. Square base outer body measuring 3.94" x 3.94" and inner metal core which, installed inside a Ø3.35" hole, can be installed on any type of support. Bard is an indoor luminaire with a minimal design, available with different LED luminous sources.

79 Trenton Avenue Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710 Fax: (908) 996-7042

## CODE COMPOSITION

example of code composition

BU1004.00 4 R 40 M \_ WD light color 27 2700K 30 3000K 40 4000K

BU1004.00 4 R 40 M 30 WD

TECHNICAL FEATURES

Code BU1004.00 XX Туре Downlight 90°  $\Delta$ Material 00: Coral® Weight 1.76 lbs Mounting Ceiling recessed IP rating IP20

Insulation class

Cut out for plasterboard

Control gear Constant current electronic driver (not included)

Ø 3.35"

LED 500mA Lamp type **■**D Vf: 18 VDC

Lamp wattage 1 x 9W

1125 lm - 3000K Luminous efficacy Light distribution Wide beam 40°

Fitting

White 3000K White 2700K I 4000K (on request) Light colour

Light hole Ø 1.97" Voltage connection By driver (optional)

CRI 90



designplan &

### Bard Surface

