




**Technical features**



109001P







# BOOK MEDIUM

Square floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver 120-277VAC 50-60Hz, with 8 CREE XP-G2 LED. IP65 rating.



**Technical data**


Wattage	12W
IP Rating	IP65
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	NR. 8 CREE "XP-G2" LED
Screws	Stainless steel
Transformer	Electronic power supply 120-277VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	Double nickel-plated brass cable gland PG9
Power cable	3.28' neoprene power cable included
Gross weight	5.51 lbs

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
high-power led	 10°	1,152	96.00
high-power led	 30°	1,095	91.25
high-power led	 45°	1,040	86.67
<b>4000°K neutral-white</b>			
high-power led	 10°	1,200	100.00
high-power led	 30°	1,140	95.00
high-power led	 45°	1,083	90.25

**Finish color options:**



**SHORT FIXING BRACKET**














109002P

# BOOK MAXI

Square floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver 120-277VAC 50-60Hz, with 20 CREE XP-G2 LED. IP65 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
high-power led	 10°	2,880	96.00
high-power led	 30°	2,736	91.20
high-power led	 45°	2,600	86.67
<b>4000°K neutral-white</b>			
high-power led	 10°	3,000	100.00
high-power led	 30°	2,850	95.00
high-power led	 45°	2,708	90.26

**Finish color options:**

-  Textured Grey RAL 9006
-  Anthracite Grey RAL 7016
-  Matt Black (on request)

**Technical features**



**Technical data**

Wattage	30W
IP Rating	IP65
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	NR. 20 CREE "XP-G2" LED
Screws	Stainless steel
Transformer	Electronic power supply 120-277VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	Double nickel-plated brass cable gland PG9
Power cable	3.28' neoprene power cable included
Gross weight	6.17 lbs

**SHORT FIXING BRACKET**



**MEDIUM FIXING BRACKET**



**BOTH included In the standard package**

