

Technical features



IP 65	IK 08
-------	-------




701007P

CEILING MAXI

Recessed luminaire for outdoor ceiling installation, phospho-chromatized and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver xxx 50-60Hz, with 1 x COB LED. IP65 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
cob led	 30°	4,240	84.80

Finish color options:

 Matte Black

Technical data

Wattage	50 WATT
IP Rating	IP65
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	NR. 1 x 50W COB Bridgelux LED
Screws	Stainless steel
Transformer	Electronic power supply xxx 50/60Hz built-in
Gasket	Silicone rubber
Power cable	3.28' neoprene power cable included
Glass	Tempered
Gross weight	7.61 lbs



Technical features



IP 65	IK 08
-------	-------



701006P

CEILING MEDIUM

Recessed luminaire for outdoor ceiling installation, phospho-chromatized and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver xxx 50-60Hz, with 1 x COB LED. IP65 rating.



Technical data

Wattage	26 WATT
IP Rating	IP65
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	NR. 1 x 26W COB Bridgelux LED
Screws	Stainless steel
Transformer	Electronic power supply xxx 50/60Hz built-in
Gasket	Silicone rubber
Power cable	3.28' neoprene power cable included
Glass	Tempered
Gross weight	4.85 lbs

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
cob led	30°	2,745	105.58

Finish color options:

Matte Black



Technical features



IP 65	IK 08
-------	-------




701005P

CEILING MINI

Recessed luminaire for outdoor ceiling installation, phospho-chromatized and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver xxx 50-60Hz, with 1 x COB LED. IP65 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
cob led	 25°	900	75.00

Finish color options:

 Matte Black

Technical data

Wattage	12 WATT
IP Rating	IP65
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	NR. 1 x 12W COB Bridgelux LED
Screws	Stainless steel
Transformer	Electronic power supply xxx 50/60Hz built-in
Gasket	Silicone rubber
Power cable	3.28' neoprene power cable included
Glass	Tempered
Gross weight	2.76 lbs

