

COMBINA D

INTERCHANGEABLE INDOOR RECESSED DOWNLIGHTS
FOR SHOWROOMS, OFFICES AND RETAIL

In the downlight version, the practical connection system on the cover means its appearance can be customized, while its light output can be altered by applying optical filters.

BUILD THE VERSION YOU WANT IN THREE STEPS

1

CHOOSE THE FIXTURE BODY



FIXED BODY



ADJUSTABLE BODY

2

CHOOSE THE RETAINING BEZEL



ROUND BEZEL
FOR INSTALLATION FLUSH
WITH CEILING



SQUARE BEZEL
FOR INSTALLATION FLUSH
WITH CEILING



ROUND BEZEL
FOR REGRESSED
INSTALLATION



SQUARE BEZEL
FOR REGRESSED
INSTALLATION

3

LASTLY, CHOOSE THE COVER



FLAT,
ROUND COVER



FLAT,
SQUARE COVER



SHALLOW,
ROUND COVER



SHALLOW,
SQUARE COVER



DEEP,
ROUND COVER
only compatible with
the fixed body



DEEP,
SQUARE COVER
only compatible with
the fixed body

designplan™

79 Trenton Avenue
Frenchtown, NJ 08825

Tel: (908) 996-7710
Fax: (908) 996-7042



COMBINA D

INTERCHANGEABLE INDOOR RECESSED DOWNLIGHTS
FOR SHOWROOMS, OFFICES AND RETAIL



narrow medium wide elliptical diffuse

6W 500mA

11W 300mA

15W 400mA

29W 800mA



2700K 3000K 4000K



∅2.76"



2.76" x 2.76"



∅3.35"



3.35" x 3.35"



∅5.35"



5.35" x 5.35"



∅7.87"



7.87" x 7.87"

FIXED OPTICS



COMBINA D 1.0

COMBINA D 2.0

COMBINA D 3.0

COMBINA D 4.0

TILTABLE OPTICS




COMBINA D 1.1

COMBINA D 2.1

COMBINA D 3.1

COMBINA D 4.1

< COMBINA D 2.0
3000K, 11W, 30°
COMBINA D 2.1
3000K, 11W, 30°-25° + elliptical filter
black, flat, round cover,
installed flush with ceiling
Courtesy of / Désirée Divani



deep,
round cover



shallow,
round cover




flat,
round cover



deep,
square cover



shallow,
square cover



flat,
square cover

COMBINA D CAN RESPOND TO CHANGING LIGHTING NEEDS THANKS TO ITS UNIQUE CUTOUT HOLE AND INTERCHANGEABLE ELEMENTS.

AT ANY TIME, THE FIXED BODY CAN BE REPLACED WITH THE ADJUSTABLE VERSION, THE SHAPE AND FINISH OF THE COVER CAN BE CHANGED, AND THE LIGHT OUTPUT CAN BE ALTERED BY ADDING OPTICAL FILTERS

BODY IN
DIE-CAST ALUMINUM
AND BAYBLEND

RETAINING BEZEL
ENABLES INSTALLATION
TO BE REGRESS OR FLUSH
WITH CEILING

COVER
FLAT AND SHALLOW VERSIONS
COMBINED WITH DEEP-SET OPTICS
PRODUCE A LIGHT OUTPUT THAT
PROVIDES HIGH VISUAL COMFORT
WITH AN UGR <13, WHILE THE DEEP
VERSION HAS AN UGR <19

OPTICAL ACCESSORIES
THE OPTICAL FILTERS ALTER THE
OPTICS' LIGHT EFFECTS TO PRODUCE
A DIFFUSE OR ELLIPTICAL OUTPUT.
ALL FILTERS CAN BE STILL APPLIED
TO DOWNLIGHTS AFTER INSTALLATION
BECAUSE OF THE SPECIAL HOUSING
PROVIDED IN THE FIXTURE'S COVER



RAL FINISH
ON REQUEST




COMBINA D

UNIQUE SELLING POINTS



COLOR VECTOR GRAPHIC



CRI >97 AND TM-30
MAXIMUM COLOR RENDITION
THANKS TO LED LIGHT
SOURCES WITH CRI >90
AND CRI >97

REMOTE PHOSPHOR
TECHNOLOGY AND
2-STEP MACADAM
(COMBINA D 2 / 3 / 4)
GUARANTEE COLOR-BRIGHTNESS
CONSISTENCY OVER TIME

THE BLACK INTERIOR
OF THE OPTICAL
UNIT HELPS
TO CONTROL
REFLECTANCE AND
AVOID UNWANTED
REFLECTIONS

THE ADJUSTABLE VERSIONS
OF COMBINA D ALLOW
THE BODY TO BE
ROTATED THROUGH
350° AND TILTED THROUGH
30° TO DIRECT THE
LIGHT BEAM PRECISELY



EASY TO WIRE
BECAUSE ELECTRICAL
CABLES CAN BE
CONNECTED
DIRECTLY TO THE
CONNECTOR




THE PRIMER COATING
MEANS THE COVER CAN
BE FINISHED IN THE
SAME PAINT AS THE
CEILING, SO THAT THE
FIXTURE BLENDS INTO
THE BACKGROUND




COMBINA D 1



COMBINA D 1.0




Required installation accessories, not included




POWER / POWER SUPPLY MODEL NO.	6W 500mA CC10201000 ■ 0 ■ 0
CRI	CRI >90
LED COLOR	F - 2700K 5 - 3000K 9 - 4000K
OPTICS	flat/shallow cover: S - 16° M - 22° L - 33° deep cover: S - 16° M - 23° L - 42°
LUMEN OUTPUT AT SOURCE	637 lm (3000K, 500mA)
DELIVERED LUMEN OUTPUT	345 lm (3000K, 500mA, 16°)
NO. AND TYPE OF LED	1 high intensity power LED 3-step MacAdam, 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in die-cast aluminum and Bayblend bezel and cover in die-cast aluminum
POWER SUPPLY UNIT	remote power supply required, not included
POWER CABLES	includes 2x0.98' single-core PVC cables
WIRING	series
MOUNTING	recessed (ceiling)
ACCESSORIES	see accessories page
FEATURES	UGR <13 for versions with flat and shallow covers UGR <19 for versions with deep cover

COMBINA D 1.1



Required installation accessories, not included




POWER / POWER SUPPLY MODEL NO.	6W 500mA CC11201000 ■ 0 ■ 0
CRI	CRI >90
LED COLOR	F - 2700K 5 - 3000K 9 - 4000K
OPTICS	S - 16° adjustable ±30° M - 22° adjustable ±30° L - 33° adjustable ±30°
LUMEN OUTPUT AT SOURCE	637 lm (3000K, 500mA)
DELIVERED LUMEN OUTPUT	293 lm (3000K, 500mA, 16°)
NO. AND TYPE OF LED	1 high intensity power LED 3-step MacAdam, 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in die-cast aluminum and Bayblend bezel and cover in die-cast aluminum
POWER SUPPLY UNIT	remote power supply required, not included
POWER CABLES	includes 2x0.98' single-core PVC cables
WIRING	series
MOUNTING	recessed (ceiling)
ACCESSORIES	see accessories page
FEATURES	UGR <13


COMBINA D 2




COMBINA D 2.0



Required installation accessories, not included



COMBINA D 2.1



Required installation accessories, not included




POWER / POWER SUPPLY MODEL NO.	11W 300mA CC2020 ■ ■ ■ ■ ■ ■
CRI	1 - CRI >90 2 - CRI >97 (only 2700K, 3000K)
LED COLOR	F - 2700K 5 - 3000K 9 - 4000K
OPTICS	S - 25° M - 30° L - 36°
LUMEN OUTPUT AT SOURCE	960 lm (3000K, 300mA, CRI >90)
DELIVERED LUMEN OUTPUT	907 lm (3000K, 300mA, 36°, CRI >90)
NO. AND TYPE OF LED	1 high intensity power LED 2-step MacAdam, 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in die-cast aluminum and Bayblend bezel and cover in die-cast aluminum
POWER SUPPLY UNIT	remote power supply required, not included
POWER CABLES	includes 2x0.98' single-core PVC cables
WIRING	series
MOUNTING	recessed (ceiling)
ACCESSORIES	see accessories page
FEATURES	UGR <13 for versions with flat and shallow covers UGR <19 for versions with deep cover

POWER / POWER SUPPLY MODEL NO.	11W 300mA CC2120 ■ ■ ■ ■ ■ ■
CRI	1 - CRI >90 2 - CRI >97 (only 2700K, 3000K)
LED COLOR	F - 2700K 5 - 3000K 9 - 4000K
OPTICS	S - 25° adjustable ±30° M - 30° adjustable ±30° L - 36° adjustable ±30°
LUMEN OUTPUT AT SOURCE	960 lm (3000K, 300mA, CRI >90)
DELIVERED LUMEN OUTPUT	756 lm (3000K, 300mA, 36°, CRI >90)
NO. AND TYPE OF LED	1 high intensity power LED 2-step MacAdam, 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in die-cast aluminum and Bayblend bezel and cover in die-cast aluminum
POWER SUPPLY UNIT	remote power supply required, not included
POWER CABLES	includes 2x0.98' single-core PVC cables
WIRING	series
MOUNTING	recessed (ceiling)
ACCESSORIES	see accessories page
FEATURES	UGR <13


COMBINA D 3




COMBINA D 3.0




Required installation accessories, not included



COMBINA D 3.1



Required installation accessories, not included




POWER / POWER SUPPLY	15W 400mA
MODEL NO.	CC3020 ■ ■ ■ ■
■ CRI	1 - CRI >90 2 - CRI >97 (only 2700K, 3000K)
■ LED COLOR	F - 2700K 5 - 3000K 9 - 4000K
■ OPTICS	S - 18° M - 29° L - 36°
LUMEN OUTPUT AT SOURCE	1349 lm (3000K, 400mA, CRI >90)
DELIVERED LUMEN OUTPUT	1177 lm (3000K, 400mA, 36°, CRI >90)
NO. AND TYPE OF LED	1 high intensity power LED 2-step MacAdam, 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in die-cast aluminum and Bayblend bezel and cover in die-cast aluminum
POWER SUPPLY UNIT	remote power supply required, not included
POWER CABLES	includes 2x0.98' single-core PVC cables
WIRING	series
MOUNTING	recessed (ceiling)
ACCESSORIES	see accessories page
FEATURES	UGR <13 for versions with flat and shallow covers UGR <19 for versions with deep cover

POWER / POWER SUPPLY	15W 400mA
MODEL NO.	CC3120 ■ ■ ■ ■
■ CRI	1 - CRI >90 2 - CRI >97 (only 2700K, 3000K)
■ LED COLOR	F - 2700K 5 - 3000K 9 - 4000K
■ OPTICS	S - 18° adjustable ±30° M - 29° adjustable ±30° L - 36° adjustable ±30°
LUMEN OUTPUT AT SOURCE	1349 lm (3000K, 400mA, CRI >90)
DELIVERED LUMEN OUTPUT	1094 lm (3000K, 400mA, 36°, CRI >90)
NO. AND TYPE OF LED	1 high intensity power LED 2-step MacAdam, 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in die-cast aluminum and Bayblend bezel and cover in die-cast aluminum
POWER SUPPLY UNIT	remote power supply required, not included
POWER CABLES	includes 2x0.98' single-core PVC cables
WIRING	series
MOUNTING	recessed (ceiling)
ACCESSORIES	see accessories page
FEATURES	UGR <13


COMBINA D 4




COMBINA D 4.0




Required installation accessories, not included



COMBINA D 4.1



Required installation accessories, not included









POWER / POWER SUPPLY MODEL NO.	29W 800mA CC4020 000 0 0 0
CRI	1 - CRI >90 2 - CRI >97 (only 2700K, 3000K)
LED COLOR	F - 2700K 5 - 3000K 9 - 4000K
OPTICS	flat/shallow cover: S - 20° M - 29° L - 38° deep cover: S - 21° M - 30° L - 41°
LUMEN OUTPUT AT SOURCE	2829 lm (3000K, 800mA, CRI >90)
DELIVERED LUMEN OUTPUT	2363 lm (3000K, 800mA, 41°, CRI >90)
NO. AND TYPE OF LED	1 high intensity power LED 2-step MacAdam, 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in die-cast aluminum and Bayblend bezel and cover in die-cast aluminum
POWER SUPPLY UNIT	remote power supply required, not included
POWER CABLES	includes 2x0.98' single-core PVC cables
WIRING	series
MOUNTING	recessed (ceiling)
ACCESSORIES	see accessories page
FEATURES	UGR <13 for versions with flat and shallow covers UGR <19 for versions with deep cover

POWER / POWER SUPPLY MODEL NO.	29W 800mA CC4120 000 0 0 0
CRI	1 - CRI >90 2 - CRI >97 (only 2700K, 3000K)
LED COLOR	F - 2700K 5 - 3000K 9 - 4000K
OPTICS	S - 20° adjustable ±30° M - 29° adjustable ±30° L - 38° adjustable ±30°
LUMEN OUTPUT AT SOURCE	2829 lm (3000K, 800mA, CRI >90)
DELIVERED LUMEN OUTPUT	2260 lm (3000K, 800mA, 20°, CRI >90)
NO. AND TYPE OF LED	1 high intensity power LED 2-step MacAdam, 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in die-cast aluminum and Bayblend bezel and cover in die-cast aluminum
POWER SUPPLY UNIT	remote power supply required, not included
POWER CABLES	includes 2x0.98' single-core PVC cables
WIRING	series
MOUNTING	recessed (ceiling)
ACCESSORIES	see accessories page
FEATURES	UGR <13

COMBINA D





















ACCESSORIES





	COMBINA D 1	COMBINA D 2	COMBINA D 3	COMBINA D 4
<p>ACCESSORIES required installation accessories, not included</p>  <p>Flat, round cover</p>	<p>WZCC1010E White WZCC1010N Black WZCC1010Z Antique bronze WZCC10108 Primer</p>	<p>WZCC2010E White WZCC2010N Black WZCC2010Z Antique bronze WZCC20108 Primer</p>	<p>WZCC3010E White WZCC3010N Black WZCC3010Z Antique bronze WZCC30108 Primer</p>	<p>WZCC4010E White WZCC4010N Black WZCC4010Z Antique bronze WZCC40108 Primer</p>
 <p>Shallow, round cover</p>	<p>WZCC1030E White WZCC1030N Black WZCC1030Z Antique bronze WZCC10308 Primer</p>	<p>WZCC2030E White WZCC2030N Black WZCC2030Z Antique bronze WZCC20308 Primer</p>	<p>WZCC3030E White WZCC3030N Black WZCC3030Z Antique bronze WZCC30308 Primer</p>	<p>WZCC4030E White WZCC4030N Black WZCC4030Z Antique bronze WZCC40308 Primer</p>
 <p>Deep, round cover</p>	<p>WZCC1050E White WZCC1050N Black WZCC1050Z Antique bronze WZCC10508 Primer (Combina D 1.0)</p>	<p>WZCC2050E White WZCC2050N Black WZCC2050Z Antique bronze WZCC20508 Primer (Combina D 2.0)</p>	<p>WZCC3050E White WZCC3050N Black WZCC3050Z Antique bronze WZCC30508 Primer (Combina D 3.0)</p>	<p>WZCC4050E White WZCC4050N Black WZCC4050Z Antique bronze WZCC40508 Primer (Combina D 4.0)</p>

	COMBINA D 1	COMBINA D 2	COMBINA D 3	COMBINA D 4
<p>ACCESSORIES required installation accessories, not included</p>  <p>Flat, square cover</p>	<p>WZCC1020E White WZCC1020N Black WZCC1020Z Antique bronze WZCC10208 Primer</p>	<p>WZCC2020E White WZCC2020N Black WZCC2020Z Antique bronze WZCC20208 Primer</p>	<p>WZCC3020E White WZCC3020N Black WZCC3020Z Antique bronze WZCC30208 Primer</p>	<p>WZCC4020E White WZCC4020N Black WZCC4020Z Antique bronze WZCC40208 Primer</p>
 <p>Shallow, square cover</p>	<p>WZCC1040E White WZCC1040N Nero WZCC1040Z Antique bronze WZCC10408 Primer</p>	<p>WZCC2040E White WZCC2040N Nero WZCC2040Z Antique bronze WZCC20408 Primer</p>	<p>WZCC3040E White WZCC3040N Nero WZCC3040Z Antique bronze WZCC30408 Primer</p>	<p>WZCC4040E White WZCC4040N Nero WZCC4040Z Antique bronze WZCC40408 Primer</p>
 <p>Deep, square cover</p>	<p>WZCC1060E White WZCC1060N Black WZCC1060Z Antique bronze WZCC10608 Primer (Combina D 1.0)</p>	<p>WZCC2060E White WZCC2060N Black WZCC2060Z Antique bronze WZCC20608 Primer (Combina D 2.0)</p>	<p>WZCC3060E White WZCC3060N Black WZCC3060Z Antique bronze WZCC30608 Primer (Combina D 3.0)</p>	<p>WZCC4060E White WZCC4060N Black WZCC4060Z Antique bronze WZCC40608 Primer (Combina D 4.0)</p>

COMBINA D

ACCESSORIES

	COMBINA D 1	COMBINA D 2	COMBINA D 3	COMBINA D 4
ACCESSORIES PRODUCT CONFIGURATION				
 <p>Round bezel for installation flush with ceiling</p>	WGCC10A1F  Ø3.07"	WGCC20A1F  Ø3.66"	WGCC30A1F  Ø5.71"	WGCC40A1F  Ø8.27"
 <p>Square bezel for installation flush with ceiling</p>	WGCC10A2F  3.07"x3.07"	WGCC20A2F  3.66"x3.66"	WGCC30A2F  5.71"x5.71"	WGCC40A2F  8.27"x8.27"
 <p>Round bezel for regressed installation</p>	WGCC10A1T  Ø2.36"	WGCC20A1T  Ø2.95"	WGCC30A1T  Ø4.92"	WGCC40A1T  Ø7.36"
 <p>Square bezel for regressed installation</p>	WGCC10A2T  2.36"x2.36"	WGCC20A2T  2.95"x2.95"	WGCC30A2T  4.92"x4.92"	WGCC40A2T  7.36"x7.36"

	COMBINA D 1	COMBINA D 2	COMBINA D 3	COMBINA D 4
ACCESSORIES				
 <p>Honeycomb louvre</p>	<p>WHCC10A1 round cover: flat, shallow, deep square cover: deep</p> <p>WHCC10A2 square cover: flat, shallow</p>	<p>WHCC20A1 round cover: flat, shallow, deep square cover: deep</p> <p>WHCC20A2 square cover: flat, shallow</p>	<p>WHCC30A1 round and square covers: flat, shallow</p>	<p>WHCC40A1 round and square covers: flat, shallow</p> <p>WHCC40A3 round and square covers: deep</p>
 <p>Diffuser filter</p>	<p>WRCC10R1D round cover: flat, shallow, deep square cover: deep</p> <p>WRCC10S1D square cover: flat, shallow</p>	<p>WRCC20R1D round cover: flat, shallow, deep square cover: deep</p> <p>WRCC20S1D square cover: flat, shallow</p>	<p>WRCC30R1D round and square covers: flat, shallow</p>	<p>WRCC40R1D round and square covers: flat, shallow</p> <p>WRCC40R3D round and square covers: deep</p>
 <p>Elliptical filter</p>	<p>WRCC10R1W round cover: flat, shallow, deep square cover: deep</p> <p>WRCC10S1W square cover: flat, shallow</p>	<p>WRCC20R1W round cover: flat, shallow, deep square cover: deep</p> <p>WRCC20S1W square cover: flat, shallow</p>	<p>WRCC30R1W round and square covers: flat, shallow</p>	<p>WRCC40R1W round and square covers: flat, shallow</p> <p>WRCC40R3W round and square covers: deep</p>
 <p>Transparent IP44 screen</p>	<p>WRCC10R1T round cover: flat, shallow, deep square cover: deep</p> <p>WRCC10S1T square cover: flat, shallow</p>	<p>WRCC20R1T round cover: flat, shallow, deep square cover: deep</p> <p>WRCC20S1T square cover: flat, shallow</p>	<p>WRCC30R1T round and square covers: flat, shallow</p>	<p>WRCC40R1T round and square covers: flat, shallow</p> <p>WRCC40R3T round and square covers: deep</p>

