designplan

ILLUMINATED BICYCLE RACK/BOLLARD

datasheet

The E-BR21 Illuminated Bicycle Rack/Bollard is a bicycle parking bollard with an opening for attachment of locks with additional accent lighting at ground level.

TECHNICAL DATA

Wattage / Input	8.4W / 9.9W (350mA)			
Power Supply	Integral			
Construction	Body: Steel / Stainless Steel			
	LED Ground Illumination Component in Aluminum,			
	sealed with Polyurethane Resin			
	Designed for feed-through wiring			
ССТ	3000K, 4000K			
CRI	>80			
Optics	Ground Illumination Component: Diffuse			
Finish	Silver Gray Polyester Powder Coated (DB 703),			
	other RAL colors upon request			
Fixture Dimensions	Ø4.5" x 35.4" h			
Fixture Weight	24.25 lbs			
LED Source	1 LED module with 8 high-performance LEDs (Ground Illumination Component)			
Color Consistency	3-Step MacAdam			
Operating Temp.	-13°F to +122°F			
IP Rating	IP66			
Impact Rating	IK10			


(Right) Uplight Component When opted note interior trim of bike rack will have a white finish. (NOT STANDARD)







Fixture Dimensions Ø4.5" x 35.4"h



Flange Base

ORDERING INFORMATION

Example: E-BR21-3011901.

Model No.		ССТ	Finish	Options
E-BR21-3011901	Illuminated - Flush Mount with Buried Base	4000K	Silver Gray	Uplight component
E-BR21-3011905 Illuminated - Surface Mount with Flange Base			Consult factory	
E-BR21-3011909	Non Illuminated - Flush Mount with Buried Base		for Custom RAL	
E-BR21-3011910	Non Illuminated - Surface Mount with Flange Base			

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

1 of 1