

Technical features



Technical data


| | |
|----------------|--|
| Wattage | 14W |
| IP Rating | IP65 |
| IK Rating | IK08 |
| Material | High corrosion resistance die-cast copper-free aluminum body |
| Coating | Polyester powder coating with phosphocromating pre-finish |
| Light source | Low-power CREE LED |
| Screws | Stainless steel |
| Transformer | Electronic power supply 120VAC 50-60Hz built-in |
| Gasket | Silicone rubber |
| Rubber grommet | M16 Rutaseal® in EPDM |
| Diffuser | Polycarbonate |
| Gross weight | 3.3 lbs |

401706P

ECLIPSE MEDIUM SQUARE

Designed by PAOLO VILLA

Square wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, frosted polycarbonate diffuser, molded silicone gasket and stainless steel screws. Built-in LED driver 120VAC 50-60Hz, with low-power CREE LED. IP65 rating.



| light source* | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|--------------------------|--|-------------------|------------------------|
| 3000°K warm-white | | | |
| low power led | <input checked="" type="checkbox"/> 360° | 636 | 45.42 |

* Other light colors available on request: Neutral-white

Finish color options:

