



# GAP



## CONTINUOUS AND INDIRECT LIGHT SYSTEM.

When light has to be the main protagonist: Gap totally integrates with all surfaces, giving way to the light beam: linearity, geometry, simplicity for a never ordinary precision which tells something new to those who are looking at it.


Gap is a continuous line modular system made of AirCoral<sup>®</sup>, able to define both wall and ceiling architectural spaces and volumes creating blades of light which exalt adjacent surfaces with their wall-washer effect. The particular overlapping of light sources avoids any kind of shadow cone: once installed, Gap is studied to become an integral part of false ceilings.



79 Trenton Avenue  
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710  
Fax: (908) 996-7042




### TECHNICAL FEATURES | BODYFRAME

Code	BU8300.AC (fig. A)	BU8310.AC (fig. A)
Material	AC: AirCoral <sup>®</sup>	AC: AirCoral <sup>®</sup>
Absorption capacity*	206.88 ft <sup>2</sup>	206.88 ft <sup>2</sup>
Weight	5.51 lbs	5.51 lbs
Mounting	Ceiling recessed	Wall recessed
IP rating	-	-
Cut out for plasterboard	45.28" for each module installed	45.28" for each module installed
Light hole	-	-

### TECHNICAL FEATURES | CLOSURE HEADPART


Code	BU8350.AC (fig. B)
Material	AC: AirCoral <sup>®</sup>
Absorption capacity*	9.69 ft <sup>2</sup>
Weight	-
Mounting	Ceiling and wall recessed
IP rating	-




### TECHNICAL FEATURES | ANGLE

Code	BU8330.AC (fig. C)	BU8340.AC (fig. D)
Material	AC: AirCoral <sup>®</sup>	AC: AirCoral <sup>®</sup>
Absorption capacity*	53.8 ft <sup>2</sup>	53.8 ft <sup>2</sup>
Weight	2.87 lbs	2.87 lbs
IP rating	-	-
Note	Internal angle	External angle

C. INTERNAL ANGLE



D. EXTERNAL ANGLE



### TECHNICAL FEATURES | PROTECTION SHIELD

Code	BU8320
Material	Satin polycarbonate
Dimensions	-
Note	Suitable only for LED light source (code BU8108)

\* The absorption capacity per m<sup>3</sup> calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m<sup>2</sup>



Private villa - Madonna di Campiglio

TECHNICAL FEATURES | LIGHT SOURCE

Code	<b>BU8108</b>
Type	Downlight 90°   Wall recessed 90° 
Weight	-
IP rating	IP40
Control gear	Constant voltage driver (not included)
Lamp type	LED 24VDC (35.43°) 
Lamp wattage	1 x 21W
Luminous efficacy	2100 lm
Light distribution	Wide beam 120°
Fitting	-
Light color	White 3000K White 2700K (on request)
Light hole	-
Voltage connection	By driver (optional)
CRI	>90

EXAMPLE OF INSTALLATION

