
GENIUS BASIC NAKED IP65


THE MOST COMPACT TO INSTALL ON ANY MATERIAL.


The outdoor version of Genius Basic Naked is now available in the Basic Naked IP65 model. This totally recessed luminaire for outdoor use has been engineered to achieve an IP65 protection level. Since it is a new version of the Naked model, this product extends the concept of total surface integration to any material and contexts and also achieves the potentials typical of the Basic line.

Genius Basic Naked IP65 is a very compact product, a synthesis of Buzzi & Buzzi research in terms of versatility, efficiency and reliability: a light flow of 540 lm, installable in a cavity of only 3.15" (80 mm), with IP65 protection. It can also be installed from above onto wood, cement, mirror, marble and industrial <u>modules</u> with a thickness of from 0.47" (12 mm) to a maximum of 1.18" (30 mm). Typically Genius, the only visible part is the light emission hole measuring 0.79" (20 mm), from which the LED light source can be pulled out thanks to a system which makes it easy to replace the light source, so there is no need for any inspection hatch, nor for invasive

maintenance.










2.56" 3.15"



CODE COMPOSITION

BU207 1 BL 4 R 24 E _ WD

2700K
3000K
4000K

example of code composition

BU2071 BL 4 R 24 E **30** WD

Outdoor

TECHNICAL FEATURES

Code	BU
Туре	Dov
	\wedge
Material	Alur
Finishing	Blac
Weight	1.4
Mounting	Ceil
IP rating	IP6
Control gear	Ren elec (not
Lamp type	LEC #D
Lamp wattage	4W
Luminous efficacy	11(
Light distribution	Wid
Fitting	-
Light colour	Whi Whi (on
Light hole	ØO
Voltage connection	By
CRI	>90
Note	Suit

BU2071 XX Downlight 90°

Aluminum I Steel Black 1.43 lbs Ceiling recessed IP65

Remote constant current electronic driver (not included) LED 700mA ID Vf: 6.5 VDC

4W 110 lm/W - 3000K

Wide beam 24°

White 3000K White 2700K | 4000K (on request) Ø 0.79"

By driver (optional) >90

Suitable for installation on surfaces max 0.79" deep.