I-Lantern (Garden Lamp)



datasheet

I-Lantern is an IP65-rated luminaire that can be used as a bollard, a garden lamp or wall-mounted. The i-Lantern garden lamp comes in 2 sizes and is suitable for outdoor installations in parks and gardens. The portable i-Lantern is fitted with a red leather handle, which allows for moving and positioning the device in its desired location. Available in a rechargable version with 3 hours of power.

TECHNICAL DATA

I LOI INICAL DAIA					
Wattage	12.5W (standard version) 4W (rechargeable version)				
Power Supply	Integral 120-277VAC - 0-10V Dimming				
Construction	Body: Die-Cast and Extruded Aluminum Lens: Opal Polycarbonate Handle: Red Leather with Chromed Elements				
CCT	2700K, 3000K				
BUG Rating	B0-U1-G0				
CRI	>90				
Delivered Lumens	700 lm (3000K) 220 lm (rechargeable version)				
Efficacy	56 lm/W (3000K) 55 lm/W (rechargeable version)				
Optics	Diffuse				
Finishes	5 Standard, See Below				
Fixture Dimensions	5.91" x 5.91" x 11.9" OR 20.9" h 3.0" handle				
Lumen Maintenance	L70 >50,000hrs (Ta 40°C)				
Color Consistency	3-Step MacAdam				
IP Rating	IP65				
Impact Resistance	IK08				





Fixture Dimensions - See page 2

ORDERING INFORMATION

Example: LN75PORDHBBZV.US. Accessories / Power Supplies ordered separately.

	D				. US
Model No.	Optics	ССТ	Power	Finish	
LN70POR - 11.9" height	D - Diffuse	Y - 2700K	BBZ - standard version	L - Graphite	US
LN75POR - 20.9" height		H - 3000K	B40 - rechargeable version	V - Oxide	
NOTE: Rechargeable version comes with 3.7 VDC Li-lon battery & charging port: USB TYPE-C 5 VDC-1A 3 (charger sold separately - see page 2)				U - White G - Black H - Gray	

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042


1 of 2

I-Lantern (Garden Lamp)




datasheet


FIXTURE DIMENSIONS



PHOTOMETRIC DATA

Note: All photometric data is 3000K





ACCESSORIES







LN0409BT051USB Charger for Rechargable Version

Job Name/Date:

Fixture Type Designation: