

I-LANTERN (Pole)


I-Lantern is an IP65-rated luminaire that can be used as a bollard, a garden lamp, wall-mounted or pole-mounted. The i-Lantern pole-mounted version has a height of 78.7" and comes in 2 wattages. I-Lantern pole-mounted is suitable for outdoor installation such as driveways or gardens and can be controlled via Bluetooth. Dark Sky compliant for output below 80°.



TECHNICAL DATA

LED Wattage / Total	10W LED, 12.5W total 24W LED, 26W total
Power Supply	Integral 120-277VAC - 0-10V Dimming
Construction	Body: Die-Cast and Extruded Aluminum Lens: Opal Polycarbonate
CCT	3000K
BUG Rating	B0-U0-G0
CRI	>90
Delivered Lumens	600 lm (12.5W - 3000K) 1170 lm (24W - 3000K) Dark Sky compliant, output below 80°
Efficacy	48 lm/W (12.5W - 3000K) 45 lm/W (24W - 3000K)
Optics	Diffused
Finishes	4 Standard, See Below
Fixture Dimensions	5.91" x 5.91" x 78.9" h
Lumen Maintenance	L70 >50,000hrs (Ta 40°C)
Color Consistency	3-Step MacAdam
IP Rating	IP65
Impact Resistance	IK08

Fixture Dimensions



ORDERING INFORMATION

Example: LN70200DHB10V.US. Accessories ordered separately.

<input type="text"/>	<input type="text"/>	<input type="text" value="US"/>
Model No.	Finish	<input type="text"/>
LN70200DHB10 - 12.5W version	L - Graphite	US
LN71200DHB10 - 26W version	V - Oxide	
	U - White	
	G - Black	

Job Name/Date:

Fixture Type Designation:

ACCESSORIES - Installation



LN00ALN
Root Mounting Plate Assembly
For use when mounting in soil





LN00ALN.01P
Anchor Bolt Assembly
For use with concrete footing



PHOTOMETRIC DATA

Note: All photometric data is 3000K

10W



24W



Job Name/Date:

Fixture Type Designation: