

# ICE LED

## **OUTDOOR STEP LIGHTS** LIGHT POINT FOR GARDENS AND FLOWERBEDS







ICE LED 1.0

ICE LED 1.1




**MATERIAL** 

WIRING MOUNTING

**ACCESSORIES** 

POWER SUPPLY UNIT




body in anodized aluminum and sandblasted glass

remote power supply required, not included

recessed (wall, ground) surface mounted (ground)

see accessories page





1102.3 lbs	0.9 lbs	IP67	IK07
LED	(IPS) (Tr	nax 40°C	

1W	350m	Α		
LE1	111	D.	Α١	١

POWER / POWER SUPPLY MODEL NO.	1W 350mA <b>LE1011</b> ■ <b>D A V</b> - ■
LED COLOR	F - 2700K 5 - 3000K 9 - 4000K 0 - 5000K 1 - blue
■ POWER CABLES	includes 4.92' neoprene cable H05RN-F 0.08"x0.01"/0.03" Ø0.25" 1 - 16.40' 2 - 32.81' 3 - 49.21' 4 - 65.62'
OPTICS	diffuse
LUMEN OUTPUT AT SOURCE	110 lm (3000K, 350mA)
DELIVERED LUMEN OUTPUT	89 lm (3000K, 350mA)
NO. AND TYPE OF LED	1 power LED 1/4 ANSI BIN (white LED color) 50000h L90 B10 (Ta 25°C)


		LEIIII DAV-
	•	F - 2700K 5 - 3000K 9 - 4000K 0 - 5000K 1 - blue
	•	includes 4.92' neoprene cable H05RN-F 0.08"x0.01"/0.03" Ø0.25" 1 - 16.40' 2 - 32.81' 3 - 49.21' 4 - 65.62'
		diffuse
		110 lm (3000K, 350mA)
		89 lm (3000K, 350mA)


1 p 1/2 50	power LED 4 ANSI BIN (white LED color) 000h L90 B10 (Ta 25°C)
bo	dy in anodized aluminum and sandblasted glass
rer	note power supply required, not included
sei	ries
	cessed (wall, ground) rface mounted (ground)
se	e accessories page

# **ICE LED**

## **ACCESSORIES AND POWER SUPPLY UNITS**

#### ACCESSORIES FOR INSTALLATION





WC0410

Outer casing (Ice LED 1.0)

WC0411 Outer casing (Ice LED 1.1)

#### **POWER CABLES**

the choice of power cable is included in the configuration of the code for the lighting fixture

- -1 16.40'
- -2 32.81'
- -3 49.21'
- -4 65.62'

Neoprene cables H05RN-F 0.08"x0.01"/0.03" Ø0.25" IPS

# **ICE LED**

## **PHOTOMETRY**

ICE LED 1.0 1.1 **D**- Diffuse

Fc max (3000K) H (ft) Ø (ft) 3.84' 1.64' 8.1 7.64' 3.28' 2.0 11.48' 4.92' 0.9 15.32' 6.56' 0.6 8.20' 19.13'

