

Luminaire designed for wall and ceiling installation. Suitable for LED sources, it is composed of a body made of polyester powder coated aluminum sheet to ensure durability over time and maximum resistance against atmospheric agents. A specific transparent crystal-clear diffuser screen in PMMA, submitted to a processing treatment from solid, ensures a perfect uniformity of light distribution and performance. The screen is integral to the body through a special glue-sealant used in shipbuilding. The installation is allowed through a hidden installation plate in stainless steel sheet by hidden fixing screws. Protection degree IP65 of these luminaires is ensured by a special glue-sealant used in shipbuilding and appropriate waterproof cable gland system. It is equipped with a 1.64' long cable for connection to the 24VDC power supply line. ADA Compliant.



PHANTOM LINEAR
















TECHNICAL DRAWING



11.81" x 3.94" x H2.36"



23.62" x 3.94" x H2.36"




35.43" x 3.94" x H2.36"

PHANTOM LINEAR

model	code	dimension	lamp	lumens			1
				2700K	3000K	4000K	
PHANTOM LINEAR 1	LM01.104458.US	3.94" x 11.81" x H2.36"	LED 6.5W	945	996	1027	
PHANTOM LINEAR 2	LM01.104459.US	3.94" x 23.62" x H2.36"	LED 13W	1890	1992	2054	
PHANTOM LINEAR 3	LM01.104460.US	3.94" x 35.43" x H2.36"	LED 19.5W	2835	2988	3082	

EXAMPLE OF CODE COMPOSITION



Light beam					
.DI	diffused				
LED Color					
.BC	2700K				
.BP	3000K				
BF	4000K				

FINISH

color	code	color	code	color	code
	.01 / painted white		.02 / painted black		.03 / painted grey
	.04 / painted cor-ten		.11 / painted anthracite		





