designplan™
79 Trenton Avenue
Frenchtown, NJ 08825
www.designplan.com
Tel: (908) 996-7710
Fax: (908) 996-7042

^
NEVA 1.2
2700K, 45W, 10°x40°
with honeycomb louvre, customized version with CRI >90

	2700K 3000K 4000K **LED SPACING 2.36"**	2700K 3000K 4000K **LED SPACING 4.72"**	2700K 3000K 4000K **LED SPACING 2.36"** **BUILT-IN POWER SUPPLY UNIT**
12.44"	 **NEVA MINI 1** 9W/13W 24VDC	 **NEVA MINI 2** 5.5W/7.5W 24VDC	
24.25" **26.65"**	 **NEVA 1.0** 18W/25W 24VDC	 **NEVA 2.0** 11W/15W 24VDC	 **NEVA 3.0** 23W 120VAC 0-10V, ON/OFF
36.06" **40.83"**	 **NEVA 1.1** 27W/38W 24VDC	 **NEVA 2.1** 16W/22W 24VDC	 **NEVA 3.1** 39W 120VAC 0-10V, ON/OFF
1517 mm **1758 mm**	 **NEVA 1.2** 45W/63W 24VDC	 **NEVA 2.2** 27W/38W 24VDC	 **NEVA 3.2** 64W 120VAC ON/OFF

NEVA

OUTDOOR LINEAR PROFILES
ARCHITECTURAL LIGHTING FOR WALLS AND FACADES

narrow medium wide ultra-wide elliptical

2700K 3000K 4000K

LED SPACING 4.72"
BUILT-IN POWER SUPPLY UNIT

RGB

LED SPACING 4.72"

DYNAMIC WHITE

LED SPACING 4.72"

RGBW

LED SPACING 4.72"

NEVA MINI 5
10W 24VDC

NEVA MINI 6
10W 24VDC

NEVA MINI 7
15W 24VDC

NEVA 4.0
16W 120VAC
0-10V, ON/OFF

NEVA 5.0
20W 24VDC
with or without DMX

NEVA 6.0
20W 24VDC

NEVA 7.0
30W 24VDC

NEVA 4.1
24W 120VAC
0-10V, ON/OFF

NEVA 5.1
30W 24VDC

NEVA 6.1
30W 24VDC

NEVA 7.1
45W 24VDC

NEVA 4.2
40W 120VAC
0-10V, ON/OFF

NEVA 5.2
50W 24VDC

NEVA 6.2
50W 24VDC

NEVA 7.2
75W 24VDC

NEVA 1 / 3

11°

30°

45°

10°x40°

NEVA 2 / 4

11°

30°

45°

10°x40°

ANTI-GLARE
RECESSED
OPTICS

IK06
NEVA 1 / 2
5 / 6 / 7

IK08
NEVA
3 / 4

TEMPERED TRANSPARENT
EXTRA-CLEAR GLASS WITH
VITRIFIED SERIGRAPHY
AND HIGH TRANSMITTANCE
TO ENSURE CHROMATIC
UNIFORMITY OF LIGHT. THE GLASS'S
THICKNESS OF 0.16" GUARANTEES
HIGH IMPACT RESISTANCE

LOW-COPPER-CONTENT
ANTICORODAL ALUMINUM
ALLOY 6060 FOR EXCELLENT
CORROSION RESISTANCE AND
IMPROVED HEAT DISSIPATION.
THE ANODIZATION PROCESS
PROTECTS THE FIXTURE'S
FUNCTIONING AND APPEARANCE
FROM ATMOSPHERIC AND
ENVIRONMENTAL AGENTS

NEVA

UNIQUE SELLING POINTS

BUILT-IN
PROTECTION
SYSTEMS:

IPS
INTELLIGENT
PROTECTION
SYSTEM

PID
PROTECTIVE
IMPEDANCE
DEVICE

NTC
BUILT-IN
TEMPERATURE
SENSOR

IP65
IP67

SUITABLE
FOR OUTDOOR
APPLICATIONS

NEVA 1 / 3
LED SPACING
CONSISTENCY
BETWEEN DEVICES
PLACED SIDE BY SIDE

NEVA 3 / 4
IP68 CONNECTOR WITH
BUILT-IN IPS PROTECTION
Speedy installation: electrical wiring simplified by the ability to connect the electrical cables directly to the connector. An in/out connection system is available to install the fixtures in a line

RECESSED
INSTALLATION
USING DEDICATED
OUTER CASING

SCALED ADJUSTABLE
BRACKET AND
TWO DIFFERENT
HEIGHTS:
2.95", 5.51"

ANTI-GLARE
HONEYCOMB
LOUVRE ACCESSORY

^

NEVA 1.1
2700K, 27W, 10°x40°, with honeycomb louvre customized version with CRI >90

KLEO 1.0
2700K, 10W, 30°, cor-ten, with spike

BRIGHT 1.6
2700K, 2W, 10°

Light planning by / Susanna Antico
Lighting Design Studio
Cascina Ranverso
Buttigliera Alta, Turin, Italy

NEVA MINI 1

1.30 lbs IP67 IK06
IPS PID NTC T max 113°F

POWER / POWER SUPPLY MODEL NO.	9W 24VDC 12.44" LED spacing 2.36" **NV0100** ■ ■ **A -** ■ 13W 24VDC 12.44" LED spacing 2.36" **NV0101** ■ ■ **A -** ■
■ **LED COLOR**	**F** - 2700K **5** - 3000K **9** - 4000K
■ **OPTICS**	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
■ **POWER CABLES**	**0** - includes 4.92' neoprene cable H05RN-F 2x0.03" Ø0.25" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
LUMEN OUTPUT AT SOURCE	696 lm (3000K, 9W) 1033 lm (3000K, 13W)
DELIVERED LUMEN OUTPUT	575 lm (3000K, 30°, 9W) 805 lm (3000K, 30°, 13W)
NO. AND TYPE OF LED	5 power LEDs - spacing 2.36" 3-step MacAdam, 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
POWER SUPPLY UNIT	remote power supply required, not included
MOUNTING	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 1.0

2.54 lbs IP67 IK06
IPS PID NTC T max 113°F

	18W 24VDC 24.25" LED spacing 2.36" **NV1000** ■ ■ **A -** ■ 25W 24VDC 24.25" LED spacing 2.36" **NV1001** ■ ■ **A -** ■
■	**F** - 2700K **5** - 3000K **9** - 4000K
■	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
■	**0** - includes 4.92' neoprene cable H05RN-F 2x0.03" Ø0.25" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
	1392 lm (3000K, 18W) 2065 lm (3000K, 25W)
	1150 lm (3000K, 30°, 18W) 1610 lm (3000K, 30°, 25W)
	10 power LEDs - spacing 2.36" 3-step MacAdam, 50,000h L90 B10 (Ta 25°C)
	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
	remote power supply required, not included
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 1

NEVA 1.1

3.62 lbs IP67 IK06

IPS PID NTC T max 113°F

27W 24VDC 36.06" LED spacing 2.36"
NV1100 ■ ■ **A -** ■

38W 24VDC 36.06" LED spacing 2.36"
NV1101 ■ ■ **A -** ■

■ **F** - 2700K
5 - 3000K
9 - 4000K

■ **S** - 11°
M - 30°
L - 45°
W - 10°x40°

■ **0** - includes 4.92' neoprene cable H05RN-F 2x0.03" Ø0.25"
1 - 16.40'
2 - 32.81'
3 - 49.21'
4 - 65.62'

2087 lm (3000K, 27W)
3098 lm (3000K, 38W)

1715 lm (3000K, 30°, 27W)
2401 lm (3000K, 30°, 38W)

15 power LEDs - spacing 2.36"
3-step MacAdam, 50,000h L90 B10 (Ta 25°C)

body in anodized anticorodal aluminum
lens in serigraphed, tempered, transparent extra-clear glass

remote power supply required, not included

surface mounted (ceiling, wall, ground) with brackets
recessed (ceiling, wall, ground) with outer casing

NEVA 1.2

6.06 lbs IP67 IK06

IPS PID NTC T max 113°F

45W 24VDC 59.72" LED spacing 2.36"
NV1200 ■ ■ **A -** ■

63W 24VDC 59.72" LED spacing 2.36"
NV1201 ■ ■ **A -** ■

■ **F** - 2700K
5 - 3000K
9 - 4000K

■ **S** - 11°
M - 30°
L - 45°
W - 10°x40°

■ **0** - includes 4.92' neoprene cable H05RN-F 2x0.03" Ø0.25"
1 - 5 m
2 - 10 m
3 - 15 m
4 - 20 m

3479 lm (3000K, 45W)
5163 lm (3000K, 63W)

2875 lm (3000K, 30°, 45W)
4025 lm (3000K, 30°, 63W)

25 power LEDs - spacing 2.36"
3-step MacAdam, 50,000h L90 B10 (Ta 25°C)

body in anodized anticorodal aluminum
lens in serigraphed, tempered, transparent extra-clear glass

remote power supply required, not included

surface mounted (ceiling, wall, ground) with brackets
recessed (ceiling, wall, ground) with outer casing

^
NEVA 2.0
3000K, 11W, 45°, with brackets
BRIGHT 2.4
3000K, 7W, 11° - 45°, stainless steel

Project by / arch. Fernanda Cantone
Light planning by / Light Style
Castello Tafuri Charming Suites
Portopalo di Capo Passero
Syracuse, Italy

NEVA MINI 2

1.28 lbs IP67 IK06
IPS PID NTC T max 113°F

POWER / POWER SUPPLY MODEL NO.	5.5W 24VDC 12.44" LED spacing 4.72" **NV0200** ■ ■ **A -** ■ 7.5W 24VDC 12.44" LED spacing 4.72" **NV0201** ■ ■ **A -** ■
■ **LED COLOR**	**F** - 2700K **5** - 3000K **9** - 4000K
■ **OPTICS**	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
■ **POWER CABLES**	**0** - includes 4.92' neoprene cable H05RN-F 2x0.03" Ø0.25" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
LUMEN OUTPUT AT SOURCE	418 lm (3000K, 5.5W) 620 lm (3000K, 7.5W)
DELIVERED LUMEN OUTPUT	345 lm (3000K, 30°, 5.5W) 483 lm (3000K, 30°, 7.5W)
NO. AND TYPE OF LED	3 power LEDs - spacing 4.72" 3-step MacAdam 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
POWER SUPPLY UNIT	remote power supply required, not included
MOUNTING	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 2.0

2.76 lbs IP67 IK06
IPS PID NTC T max 113°F

	11W 24VDC 26.65" LED spacing 4.72" **NV2000** ■ ■ **A -** ■ 15W 24VDC 26.65" LED spacing 4.72" **NV2001** ■ ■ **A -** ■
■	**F** - 2700K **5** - 3000K **9** - 4000K
■	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
■	**0** - includes 4.92' neoprene cable H05RN-F 2x0.03" Ø0.25" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
	835 lm (3000K, 11W) 1239 lm (3000K, 15W)
	690 lm (3000K, 30°, 11W) 966 lm (3000K, 30°, 15W)
	6 power LEDs - spacing 4.72" 3-step MacAdam 50,000h L90 B10 (Ta 25°C)
	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
	remote power supply required, not included
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 2

NEVA 2.1

4.12 lbs IP67 IK06

IPS PID NTC T max 113°F

	16W 24VDC 40.83" LED spacing 4.72" **NV2100** ■ ■ **A -** ■ 22W 24VDC 40.83" LED spacing 4.72" **NV2101** ■ ■ **A -** ■
■	**F** - 2700K **5** - 3000K **9** - 4000K
■	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
■	**0** - includes 4.92' neoprene cable H05RN-F 2x0.03" Ø0.25" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
	1252 lm (3000K, 16W) 1859 lm (3000K, 22W)
	1035 lm (3000K, 30°, 16W) 1450 lm (3000K, 30°, 22W)
	9 power LEDs - spacing 4.72" 3-step MacAdam 50,000h L90 B10 (Ta 25°C)
	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
	remote power supply required, not included
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 2.2

6.94 lbs IP67 IK06

IPS PID NTC T max 113°F

	27W 24VDC 69.21" LED spacing 4.72" **NV2200** ■ ■ **A -** ■ 38W 24VDC 69.21" LED spacing 4.72" **NV2201** ■ ■ **A -** ■
■	**F** - 2700K **5** - 3000K **9** - 4000K
■	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
■	includes 4.92' neoprene cable H05RN-F 2x0.03" Ø0.25" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
	2087 lm (3000K, 27W) 3098 lm (3000K, 38W)
	1725 lm (3000K, 30°, 27W) 2415 lm (3000K, 30°, 38W)
	15 power LEDs - spacing 4.72" 3-step MacAdam 50,000h L90 B10 (Ta 25°C)
	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
	remote power supply required, not included
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 3

NEVA 3.0

3.53 lbs IP65 IP67 IK08

IPS PID T max 113°F

POWER / POWER SUPPLY MODEL NO.	23W 120VAC 24.25" LED spacing 2.36" ON/OFF **NV3010000 ■ ■ 0 ■ N** 23W 120VAC 24.25" LED spacing 2.36" 0-10V **NV30100V0 ■ ■ 0 ■ N**
■ **HONEYCOMB LOUVRE**	**0** - not present **1** - present
■ **LED COLOR**	**F** - 2700K **5** - 3000K **9** - 4000K
■ **OPTICS**	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
LUMEN OUTPUT AT SOURCE	2570 lm (3000K)
DELIVERED LUMEN OUTPUT	1610 lm (3000K, 30°)
NO. AND TYPE OF LED	10 power LEDs - spacing 2.36" 3-step MacAdam, 50,000h L85 B10 (Ta 25°C)
MATERIAL	body in black-anodized anticorodal aluminum lens in serigraphed, tempered, transparent, extra-clear glass
POWER SUPPLY UNIT	built in
MOUNTING	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing
FEATURES	electrical wiring simplified by the ability to connect the electrical cables directly to the connector

NEVA 3.1

4.63 lbs IP65 IP67 IK08

IPS PID T max 113°F

	39W 120VAC 36.06" LED spacing 2.36" ON/OFF **NV3110000** ■ ■ **0** ■ **N** 39W 120VAC 36.06" LED spacing 2.36" 0-10V **NV31100V0** ■ ■ **0** ■ **N**
■	**0** - not present **1** - present
■	**F** - 2700K **5** - 3000K **9** - 4000K
■	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
	3855 lm (3000K)
	2401 lm (3000K, 30°)
	15 power LEDs - spacing 2.36" 3-step MacAdam, 50,000h L85 B10 (Ta 25°C)
	body in black-anodized anticorodal aluminum lens in serigraphed, tempered, transparent, extra-clear glass
	built in
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing
	electrical wiring simplified by the ability to connect the electrical cables directly to the connector

NEVA 3.2

7.05 lbs IP65 IP67 IK08

IPS PID T max 113°F

	64W 120VAC 59.72" LED spacing 2.36" ON/OFF **NV3210000** ■ ■ **0** ■ **N**
■	**0** - not present **1** - present
■	**F** - 2700K **5** - 3000K **9** - 4000K
■	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
	6425 lm (3000K)
	4025 lm (3000K, 30°)
	25 power LEDs - spacing 2.36" 3-step MacAdam, 50,000h L85 B10 (Ta 25°C)
	body in black-anodized anticorodal aluminum lens in serigraphed, tempered, transparent, extra-clear glass
	built in
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing
	electrical wiring simplified by the ability to connect the electrical cables directly to the connector

^
NEVA 4.0 / 4.1
3000K, 16W - 24W, 10°x40°, with brackets

NEVA 4.0

3.75 lbs IP65 IP67 IK08

IPS PID T max 113°F

POWER / POWER SUPPLY MODEL NO.	16W 120VAC 26.65" LED spacing 4.72" ON/OFF **NV4010000 ■ ■ 0 ■ N** 16W 120VAC 26.65" LED spacing 4.72" 0-10V **NV40100V0 ■ ■ 0 ■ N**
■ **HONEYCOMB LOUVRE**	**0** - not present **1** - present
■ **LED COLOR**	**F** - 2700K **5** - 3000K **9** - 4000K
■ **OPTICS**	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
LUMEN OUTPUT AT SOURCE	1542 lm (3000K)
DELIVERED LUMEN OUTPUT	966 lm (3000K, 30°)
NO. AND TYPE OF LED	6 power LEDs - spacing 4.72" 3-step MacAdam, 50,000h L85 B10 (Ta 25°C)
MATERIAL	body in black-anodized anticorodal aluminum lens in serigraphed, tempered, transparent, extra-clear glass
POWER SUPPLY UNIT	built in
MOUNTING	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing
FEATURES	electrical wiring simplified by the ability to connect the electrical cables directly to the connector

NEVA 4

NEVA 4.1

5.16 lbs IP65 IP67 IK08

IPS PID T max 113°F

	24W 120VAC 40.83" LED spacing 4.72" ON/OFF **NV4110000** ■ ■ **0** ■ **N** 24W 120VAC 40.83" LED spacing 4.72" 0-10V **NV41100V0** ■ ■ **0** ■ **N**
■	**0** - not present **1** - present
■	**F** - 2700K **5** - 3000K **9** - 4000K
■	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
	2313 lm (3000K)
	1450 lm (3000K, 30°)
	9 power LEDs - spacing 4.72" 3-step MacAdam, 50,000h L85 B10 (Ta 25°C)
	body in black-anodized anticorodal aluminum lens in serigraphed, tempered, transparent, extra-clear glass
	built in
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing
	electrical wiring simplified by the ability to connect the electrical cables directly to the connector

NEVA 4.2

7.98 lbs IP65 IP67 IK08

IPS PID T max 113°F

	40W 120VAC 69.21" LED spacing 4.72" ON/OFF **NV4210000** ■ ■ **0** ■ **N** 40W 120VAC 69.21" LED spacing 4.72" 0-10V **NV42100V0** ■ ■ **0** ■ **N**
■	**0** - not present **1** - present
■	**F** - 2700K **5** - 3000K **9** - 4000K
■	**S** - 11° **M** - 30° **L** - 45° **W** - 10°x40°
	3855 lm (3000K)
	2415 lm (3000K, 30°)
	15 power LEDs - spacing 4.72" 3-step MacAdam, 50,000h L85 B10 (Ta 25°C)
	body in black-anodized anticorodal aluminum lens in serigraphed, tempered, transparent, extra-clear glass
	built in
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing
	electrical wiring simplified by the ability to connect the electrical cables directly to the connector

^
NEVA 5.2
RGB, 50W, 24°x46°
NEVA 2.2
3000K, 27W, 11°

Project by / iarchitects
Gotha Cosmetics Headquarters
Bergamo, Italy

NEVA MINI 5

1.28 lbs IP67 IK06
IPS NTC T max 113°F

POWER / POWER SUPPLY MODEL NO.	10W 24VDC 12.44" LED spacing 4.72" **NV0500 6 ■ A - ■**
■ **OPTICS**	**S** - 15° **M** - 26° **L** - 30° **W** - 24°x46°
■ **POWER CABLES**	**0** - includes 4.92' neoprene cable 05RN-F 4x0.02" Ø0.23" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
LED COLOR	RGB
LUMEN OUTPUT AT SOURCE	454 lm: (R) 151 lm, (G) 227 lm, (B) 76 lm
DELIVERED LUMEN OUTPUT	324 lm: (R) 108 lm, (G) 162 lm, (B) 54 lm (26°)
NO. AND TYPE OF LED	3 RGB LED groups - spacing 4.72" 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
POWER SUPPLY UNIT	remote power supply required, not included
MOUNTING	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 5.0

2.76 lbs IP67 IK06 DMX RDM
IPS NTC T max 113°F

	20W 24VDC 26.65" LED spacing 4.72" **NV5000 6 ■ A - ■** 20W 24VDC + DMX512 26.65" LED spacing 4.72" **NV5001 6 ■ A**
■	**S** - 15° **M** - 26° **L** - 30° **W** - 24°x46°
■	includes 4.92' neoprene cable 05RN-F 4x0.02" Ø0.23" DMX version: includes 2x0.06" neoprene cables H05RN-F 2x0.75 Ø0.25" and 05RN-F 4x0.02" Ø0.23" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
	RGB
	908 lm: (R) 303 lm, (G) 454 lm, (B) 151 lm
	648 lm: (R) 216 lm, (G) 324 lm, (B) 108 lm (26°)
	6 RGB LED groups - spacing 4.72" 50,000h L90 B10 (Ta 25°C)
	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
	remote power supply required, not included
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 5

NEVA 5.1

4.12 lbs IP67 IK06

IPS NTC T max 113°F

30W 24VDC 40.83" LED spacing 4.72"
NV5100 6 ■ **A -** ■

■ **S** - 15°
M - 26°
L - 30°
W - 24°x46°

■ **0** - includes 4.92' neoprene cable 05RN-F 4x0.02" Ø0.23"
1 - 16.40'
2 - 32.81'
3 - 49.21'
4 - 65.62'

RGB

1363 lm: (R) 455 lm, (G) 681 lm, (B) 227 lm

972 lm: (R) 324 lm, (G) 486 lm, (B) 162 lm (26°)

9 RGB LED groups - spacing 4.72"
50,000h L90 B10 (Ta 25°C)

body in anodized anticorodal aluminum
lens in serigraphed, tempered, transparent extra-clear glass

remote power supply required, not included

surface mounted (ceiling, wall, ground) with brackets
recessed (ceiling, wall, ground) with outer casing

NEVA 5.2

6.94 lbs IP67 IK06

IPS NTC T max 45°C

50W 24VDC 69.21" LED spacing 4.72"
NV5200 6 ■ **A -** ■

■ **S** - 15°
M - 26°
L - 30°
W - 24°x46°

■ **0** -includes 4.92' neoprene cable 05RN-F 4x0.02" Ø0.23"
1 - 16.40'
2 - 32.81'
3 - 49.21'
4 - 65.62'

RGB

2271 lm: (R) 758 lm, (G) 1135 lm, (B) 378 lm

1620 lm: (R) 540 lm, (G) 810 lm, (B) 270 lm (26°)

15 RGB LED groups - spacing 4.72"
50,000h L90 B10 (Ta 25°C)

body in anodized anticorodal aluminum
lens in serigraphed, tempered, transparent extra-clear glass

remote power supply required, not included

surface mounted (ceiling, wall, ground) with brackets
recessed (ceiling, wall, ground) with outer casing

^
NEVA 6.0
dynamic white, 20W, 24°x46°

NEVA MINI 6

1.28 lbs IP67 IK06
IPS NTC T max 113°F

NEVA 6.0

2.76 lbs IP67 IK06
IPS NTC T max 113°F

POWER / POWER SUPPLY MODEL NO.	10W 24VDC 12.44" LED spacing 4.72" **NV0600 H** ■ **A -** ■	20W 24VDC 26.65" LED spacing 4.72" **NV6000 H** ■ **A -** ■
■ **OPTICS**	**S** - 15° **M** - 26° **L** - 30° **W** - 24°x46°	■ **S** - 15° **M** - 26° **L** - 30° **W** - 24°x46°
■ **POWER CABLES**	includes 4.92' neoprene cable 05RN-F 4x0.02" Ø0.23" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'	■ includes 4.92' neoprene cable 05RN-F 4x0.02" Ø0.23" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
LED COLOR	dynamic white: amber, 4000K, 5000K	dynamic white: amber, 4000K, 5000K
LUMEN OUTPUT AT SOURCE	1035 lm, amber: 258 lm 4000K: 379 lm 5000K: 398 lm (4000K)	2070 lm, amber: 517 lm 4000K: 758 lm 5000K: 795 lm (4000K)
DELIVERED LUMEN OUTPUT	737 lm, amber: 184 lm 4000K: 270 lm 5000K: 283 lm (4000K, 26°)	1475 lm, amber: 368 lm 4000K: 540 lm 5000K: 567 lm (4000K, 26°)
NO. AND TYPE OF LED	3 LED groups - spacing 4.72" 50,000h L90 B10 (Ta 25°C)	6 LED groups - spacing 4.72" 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
POWER SUPPLY UNIT	remote power supply required, not included	remote power supply required, not included
MOUNTING	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 6

NEVA 6.1

4.12 lbs IP67 IK06

IPS NTC T max 113°F

	30W 24VDC 40.83" LED spacing 4.72" **NV6100 H** ■ **A -** ■
■	**S** - 15° **M** - 26° **L** - 30° **W** - 24°x46°
■	includes 4.92' neoprene cable 05RN-F 4x0.02" Ø0.23" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
	dynamic white: amber, 4000K, 5000K
	3100 lm, amber: 774 lm 4000K: 1135 lm 5000K: 1191 lm (4000K)
	2212 lm, amber: 552 lm 4000K: 810 lm 5000K: 850 lm (4000K, 26°)
	9 LED groups - spacing 4.72" 50,000h L90 B10 (Ta 25°C)
	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
	remote power supply required, not included
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 6.2

6.94 lbs IP67 IK06

IPS NTC T max 113°F

	50W 24VDC 69.21" LED spacing 4.72" **NV6200 H** ■ **A -** ■
■	**S** - 15° **M** - 26° **L** - 30° **W** - 24°x46°
■	includes 4.92' neoprene cable 05RN-F 4x0.02" Ø0.23" **1** - 16.40' **2** - 32.81' **3** - 49.21' **4** - 65.62'
	dynamic white: amber, 4000K, 5000K
	5162 lm, amber: 1288 lm 4000K: 1890 lm 5000K: 1984 lm (4000K)
	3687 lm, amber: 920 lm 4000K: 1350 lm 5000K: 1417 lm (4000K, 26°)
	15 LED groups - spacing 4.72" 50,000h L90 B10 (Ta 25°C)
	body in anodized anticorodal aluminium lens in serigraphed, tempered, transparent extra-clear glass
	not included
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

^
NEVA 7.2
RGBW, 75W, 26°x58°

Project by / SC Servizi Integrati
Torre Bassano
Torre del Greco, Naples, Italy

NEVA MINI 7

1.43 lbs IP67 IK06
IPS PID NTC T max 140°F

NEVA 7.0

2.76 lbs IP67 IK06
IPS PID NTC T max 140°F

POWER / POWER SUPPLY MODEL NO.	15W 24VDC 12.44" LED spacing 4.72" **NV0700 7 ■ A**	30W 24VDC 26.65" LED spacing 4.72" **NV7000 7 ■ A**
■ **OPTICS**	**S** - 18° **M** - 32° **L** - 44° **K** - 78° **W** - 26°x58°	■ **S** - 18° **M** - 32° **L** - 44° **K** - 78° **W** - 26°x58°
LED COLOR	RGBW	RGBW
LUMEN OUTPUT AT SOURCE	850 lm: (R) 137 lm, (G) 300 lm, (B) 92 lm, (W) 321 lm (4000K)	1699 lm: (R) 273 lm, (G) 600 lm, (B) 184 lm (W) 642 lm (4000K)
DELIVERED LUMEN OUTPUT	525 lm: (R) 84 lm, (G) 186 lm, (B) 57 lm (W) 198 lm (4000K, 32°)	1051 lm: (R) 169 lm, (G) 371 lm, (B) 114 lm, (W) 397 lm (4000K, 32°)
NO. AND TYPE OF LED	3 RGBW LED - spacing 4.72" 50,000h L90 B10 (Ta 25°C)	6 RGBW LED groups - spacing 4.72" 50,000h L90 B10 (Ta 25°C)
MATERIAL	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
POWER SUPPLY UNIT	remote power supply required, not included	remote power supply required, not included
POWER CABLES	includes 4.92' FEP+RUB cable (equivalent to H05RN-F) 6x0.02"/0.02" Ø0.25"	includes 4.92' FEP+RUB cable (equivalent to H05RN-F6x0.02"/0.02" Ø0.25"
MOUNTING	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 7

NEVA 7.1

4.19 lbs IP67 IK06
IPS PID NTC T max 140°F

	45W 24VDC 40.83" LED spacing 4.72" **NV7100 7 ■ A**
■	**S** - 18° **M** - 32° **L** - 44° **K** - 78° **W** - 26°x58°
	RGBW
	2548 lm: (R) 410 lm, (G) 900 lm, (B) 275 lm (W) 963 lm (4000K)
	1575 lm: (R) 253 lm, (G) 556 lm (B) 171 lm (W) 595 lm (4000K, 32°)
	9 RGBW LED groups - spacing 4.72" 50,000h L90 B10 (Ta 25°C)
	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
	remote power supply required, not included
	includes 4.92' FEP+RUB cable (equivalent to H05RN-F) 6x0.02"/0.02" Ø0.25"
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA 7.2

7.05 lbs IP67 IK06
IPS PID NTC T max 140°F

	75W 24VDC 69.21" LED spacing 4.72" **NV7200 7 ■ A**
■	**S** - 18° **M** - 32° **L** - 44° **K** - 78° **W** - 26°x58°
	RGBW
	4247 lm: (R) 683 lm, (G) 1500 lm, (B) 459 lm (W) 1605 lm (4000K)
	2625 lm: (R) 422 lm, (G) 927 lm, (B) 284 lm (W) 992 lm (4000K, 32°)
	15 RGBW LED groups - spacing 4.72" 50,000h L90 B10 (Ta 25°C)
	body in anodized anticorodal aluminum lens in serigraphed, tempered, transparent extra-clear glass
	remote power supply required, not included
	includes 4.92' FEP+RUB cable (equivalent to H05RN-F) 6x0.02"/0.02" Ø0.25"
	surface mounted (ceiling, wall, ground) with brackets recessed (ceiling, wall, ground) with outer casing

NEVA

ACCESSORIES

	NEVA MINI 1	NEVA 1.0	NEVA 1.1	NEVA 1.2	NEVA MINI 2	NEVA 2.0	NEVA 2.1	NEVA 2.2	NEVA 3.0	NEVA 3.1	NEVA 3.2
ANTI-GLARE ACCESSORIES											
Honeycomb louvre built into the lighting fixture order together with the lighting fixture	**WH6001**	**WH6010**	**WH6011**	**WH6012**	**WH6002**	**WH6020**	**WH6021**	**WH6022**			
Anti-glare shield in black-painted stainless steel	**WB6500** 12.91"	**WB6510** 24.09"	**WB6511** 35.91"	**WB6512** 59.57"	**WB6500** 12.91"	**WB6520** 26.50"	**WB6521** 40.67"	**WB6522** 69.06"	**WB6510** 24.09"	**WB6511** 35.91"	**WB6512** 59.57"
ACCESSORIES FOR INSTALLATION											
Aluminum outer casing	**WC6500** 12.68"	**WC6510** 24.49"	**WC6511** 36.30"	**WC6512** 59.92"	**WC6500** 12.68"	**WC6520** 26.85"	**WC6521** 41.02"	**WC6522** 69.41"	**WC6510** 24.49"	**WC6511** 36.30"	**WC6512** 59.92"
Aluminum outer casing for plasterboard	**WC6700** 12.68"	**WC6710** 24.49"	**WC6711** 36.30"	**WC6712** 59.92"	**WC6700** 12.68"	**WC6720** 26.85"	**WC6721** 41.02"	**WC6722** 69.41"	**WC6710** 24.49"	**WC6711** 36.30"	**WC6712** 59.92"

NEVA 4.0	NEVA 4.1	NEVA 4.2	NEVA MINI 5	NEVA 5.0	NEVA 5.1	NEVA 5.2	NEVA MINI 6	NEVA 6.0	NEVA 6.1	NEVA 6.2	NEVA MINI 7	NEVA 7.0	NEVA 7.1	NEVA 7.2
			WH6002	**WH6020**	**WH6021**	**WH6022**	**WH6002**	**WH6020**	**WH6021**	**WH6022**				
WB6520 26.50"	**WB6521** 40.67"	**WB6522** 69.06"	**WB6500** 12.91"	**WB6520** 26.50"	**WB6521** 40.67"	**WB6522** 69.06	**WB6500** 12.91"	**WB6520** 26.50"	**WB6521** 40.67"	**WB6522** 69.06"	**WB6500** 12.91"	**WB6520** 26.50"	**WB6521** 40.67"	**WB6522** 69.06"
WC6520 26.85"	**WC6521** 41.02"	**WC6522** 69.41"	**WC6500** 12.68"	**WC6520** 26.50"	**WC6521** 40.67"	**WC6522** 69.41"	**WC6500** 12.68"	**WC6520** 26.85"	**WC6521** 41.02"	**WC6522** 69.41"	**WC6500** 12.68"	**WC6520** 26.85"	**WC6521** 41.02"	**WC6522** 69.41"
WC6720 26.85"	**WC6721** 41.02"	**WC6722** 69.41"	**WC6700** 12.68"	**WC6720** 26.50"	**WC6721** 40.67"	**WC6722** 69.41"	**WC6700** 12.68"	**WC6720** 26.85"	**WC6721** 41.02"	**WC6722** 69.41"	**WC6700** 12.68"	**WC6720** 26.85"	**WC6721** 41.02"	**WC6722** 69.41"

NEVA

ACCESSORIES AND POWER SUPPLY UNITS

ACCESSORIES FOR INSTALLATION

WM0601
Pair of brackets h 2.95"
(Neva 1 / 2 / 5 / 6 / 7)

WM0602
Pair of brackets h 5.51"
(Neva 1 / 2 / 5 / 6 / 7)

WMA01N
Pair of brackets h 2.95"
(Neva 3 / 4)

WMA02N
Pair of brackets h 5.51"
(Neva 3 / 4)

WN6001
Anti-fall kit

WN6005
Alignment kit for
outer casings

WFA00
2-pin female connector
for in/out connection
(on/off version) - IP68
(Neva 3 / 4)

WFA01
4-pin female connector
for in/out connection
(0-10V version) - IP68
(Neva 3.0 / 3.1 / 4.0 / 4.1 / 4.2)

POWER CABLES Neva 1 / 2 / 5 / 6

the choice of power cable is included in the configuration
of the code for the lighting fixture

-0 length 4.92'
-1 length 16.40 '
-2 length 32.81'
-3 length 49.21'
-4 length 65.62'

white LED color
Neoprene cables
H05RN-F 2x0.03" Ø0.25" IPS

RGB and dynamic white
Neoprene cables
05RN-F 4x0.02" Ø0.23" IPS

NEVA 1.0 >
3000K, 25W, 10°x40°

Light planning by / MI10studio
Photo by / Germano Borrelli
Il Vittoriale degli Italiani
Gardone Riviera, Brescia, Italy

NEVA

OUTDOOR LINEAR PROFILES

NEVA MINI 1

S - 11°

fc max (3000K)

H (ft)	Ø (ft)	9W	13W
3.28'	0.62'	1096.4	1534.9
6.56'	1.21'	274.1	383.7
9.84'	1.84'	121.8	170.6
13.12'	2.46'	68.6	96.0
16.40'	3.05'	43.9	61.4

M - 30°

fc max (3000K)

H (ft)	Ø (ft)	9W	13W
3.28'	1.64'	146.7	205.4
6.56'	3.25'	36.7	51.4
9.84'	4.89'	16.4	22.9
13.12'	6.53'	9.2	12.8
16.40'	8.17'	5.9	8.3

L - 45°

fc max (3000K)

H (ft)	Ø (ft)	9W	13W
3.28'	2.69'	93.6	130.9
6.56'	5.38'	23.4	32.8
9.84'	8.07'	10.4	14.6
13.12'	10.76'	5.9	8.2
16.40'	13.42'	3.8	5.3

W - 10°x40°

fc max (3000K)

H (ft)	Ø (ft)	Ø (ft)	9W	13W
3.28'	0.59'	2.40'	353.7	495.2
6.56'	1.18'	4.82'	88.4	123.8
9.84'	1.77'	7.22'	39.3	55.0
13.12'	2.36'	9.65'	22.1	30.9
16.40'	2.95'	12.04'	14.1	19.8

NEVA MINI 2

S - 11°

fc max (3000K)

H (ft)	Ø (ft)	5.5W	7.5W
3.28'	0.62'	657.8	921.0
6.56'	1.21'	164.4	230.2
9.84'	1.84'	73.0	102.4
13.12'	2.46'	41.3	57.6
16.40'	3.05'	26.2	36.9

M - 30°

fc max (3000K)

H (ft)	Ø (ft)	5.5W	7.7W
3.28'	1.64'	88.1	123.3
6.56'	3.25'	22.0	30.8
9.84'	4.89'	9.8	13.8
13.12'	6.53'	5.6	7.7
16.40'	8.17'	3.6	4.9

L - 45°

fc max (3000K)

H (ft)	Ø (ft)	5.5W	7.5W
3.28'	2.69'	56.0	78.6
6.56'	5.38'	13.9	19.7
9.84'	8.07'	6.1	8.7
13.12'	10.76'	3.6	4.9
16.40'	13.42'	2.2	3.2

W - 10°x40°

fc max (3000K)

H (ft)	Ø (ft)	Ø (ft)	5,5W	7,5W
3.28'	0.59'	2.40'	212.2	297.0
6.56'	1.18'	4.82'	53.0	74.2
9.84'	1.77'	7.22'	23.6	33.0
13.12'	2.36'	9.65'	13.3	18.6
16.40'	2.95'	12.04'	8.5	11.9

NEVA MINI 5

S - 15°

fc max (white*)

H (ft)	Ø (ft)	
3.28'	0.98'	101.7
6.56'	1.97'	25.4
9.84'	2.95'	11.4
13.12'	3.90'	6.4
16.40'	4.89'	4.2

M - 26°

fc max (white*)

H (ft)	Ø (ft)	
3.28'	1.54'	88.4
6.56'	3.08'	22.1
9.84'	4.63'	9.9
13.12'	6.17'	5.6
16.40'	7.68'	3.5

L - 30°

fc max (white*)

H (ft)	Ø (ft)	
3.28'	1.74'	70.5
6.56'	3.51'	17.7
9.84'	5.25'	7.9
13.12'	7.02'	4.5
16.40'	8.76'	2.9

W - 24°x46°

fc max (white*)

H (ft)	Ø (ft)	Ø (ft)	
3.28'	1.41'	2.82'	52.9
6.56'	2.82'	5.61'	13.2
9.84'	4.27'	8.43'	5.9
13.12'	5.68'	11.22'	3.3
16.40'	7.09'	14.04'	2.1

* White created by mixing the colors

NEVA MINI 6

S - 15°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	0.98'	398.0
6.56'	1.97'	99.5
9.84'	2.95'	44.2
13.12'	3.90'	24.9
16.40'	4.89'	15.9

M - 26°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	1.54'	200.8
6.56'	3.08'	50.2
9.84'	4.63'	22.3
13.12'	6.17'	12.5
16.40'	7.68'	8.0

L - 30°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	1.74'	159.1
6.56'	3.51'	39.8
9.84'	5.25'	17.7
13.12'	7.02'	9.9
16.40'	8.76'	6.3

W - 24°x46°

H (ft)	Ø (ft)	Ø (ft)	fc max (4000K)
3.28'	1.41'	2.82'	140.9
6.56'	2.82'	5.61'	35.2
9.84'	4.27'	8.43'	15.7
13.12'	5.68'	11.22'	8.8
16.40'	7.09'	14.04'	5.7

NEVA MINI 7

S - 18°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	1.02'	347.9
6.56'	2.03'	86.7
9.84'	3.05'	38.7
13.12'	4.07'	21.7
16.40'	5.09'	13.9

M - 32°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	1.84'	118.4
6.56'	3.67'	29.6
9.84'	5.51'	13.2
13.12'	7.35'	7.4
16.40'	9.19'	4.7

L - 44°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	2.62'	59.0
6.56'	5.28'	14.8
9.84'	7.91'	6.6
13.12'	10.53'	3.7
16.40'	13.19'	2.4

K - 78°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	5.28'	25.4
6.56'	10.56'	6.4
9.84'	15.81'	2.9
13.12'	21.10'	1.6
16.40'	26.38'	1.0

W - 26°x58°

H (ft)	Ø (ft)	Ø (ft)	fc max (4000K)
3.28'	1.54'	3.61'	63.5
6.56'	3.05'	7.22'	15.9
9.84'	4.59'	10.83'	7.1
13.12'	6.10'	14.44'	4.0
16.40'	7.64'	18.04'	2.6

NEVA 1.0

S - 11°

fc max (3000K)

H (ft)	Ø (ft)	18W	25W
3.28'	0.62'	2192.6	3069.6
6.56'	1.21'	548.1	767.4
9.84'	1.84'	243.6	341.1
13.12'	2.46'	137.0	191.8
16.40'	3.05'	87.7	122.8

M - 30°

fc max (3000K)

H (ft)	Ø (ft)	18W	25W
3.28'	1.64'	293.4	410.7
6.56'	3.25'	73.3	102.7
9.84'	4.89'	32.6	45.6
13.12'	6.53'	18.3	25.6
16.40'	8.17'	11.7	16.4

L - 45°

fc max (3000K)

H (ft)	Ø (ft)	18W	25W
3.28'	2.69'	187.0	261.8
6.56'	5.38'	46.7	65.5
9.84'	8.07'	20.8	29.1
13.12'	10.76'	11.7	16.4
16.40'	13.42'	7.5	10.5

W - 10°x40°

fc max (3000K)

H (ft)	Ø (ft)	Ø (ft)	18W	25W
3.28'	0.59'	2.40'	707.5	990.3
6.56'	1.18'	4.82'	176.9	247.6
9.84'	1.77'	7.22'	78.6	110.0
13.12'	2.36'	9.65'	44.2	61.9
16.40'	2.95'	12.04'	28.3	39.6

NEVA 2.0

S - 11°

fc max (3000K)

H (ft)	Ø (ft)	11W	15W
3.28'	0.62'	1315.5	1841.8
6.56'	1.21'	328.9	460.4
9.84'	1.84'	146.0	204.7
13.12'	2.46'	82.5	115.1
16.40'	3.05'	52.4	73.7

M - 30°

fc max (3000K)

H (ft)	Ø (ft)	11W	15W
3.28'	1.64'	176.1	246.5
6.56'	3.25'	44.0	61.6
9.84'	4.89'	19.5	27.4
13.12'	6.53'	11.2	15.4
16.40'	8.17'	7.3	9.9

L - 45°

fc max (3000K)

H (ft)	Ø (ft)	11W	15W
3.28'	2.69'	112.0	157.1
6.56'	5.38'	27.9	39.3
9.84'	8.07'	12.3	17.5
13.12'	10.76'	7.3	9.9
16.40'	13.42'	4.5	6.3

W - 10°x40°

fc max (3000K)

H (ft)	Ø (ft)	Ø (ft)	11W	15W
3.28'	0.59'	2.40'	424.5	594.0
6.56'	1.18'	4.82'	106.1	148.5
9.84'	1.77'	7.22'	47.2	66.0
13.12'	2.36'	9.65'	26.6	37.2
16.40'	2.95'	12.04'	17.0	23.8

NEVA 3.0

S - 11°

H (ft)	Ø (ft)	fc max (3000K)
3.28'	0.62'	3069.6
6.56'	1.21'	767.4
9.84'	1.84'	341.0
13.12'	2.46'	191.8
16.40'	3.05'	122.8

M - 30°

H (ft)	Ø (ft)	fc max (3000K)
3.28'	1.64'	410.7
6.56'	3.25'	102.7
9.84'	4.89'	45.6
13.12'	6.53'	25.6
16.40'	8.17'	16.4

L - 45°

H (ft)	Ø (ft)	fc max (3000K)
3.28'	2.69'	261.8
6.56'	5.38'	65.5
9.84'	8.07'	29.1
13.12'	10.76'	16.4
16.40'	13.42'	10.5

W - 10°x40°

H (ft)	Ø (ft)	Ø (ft)	fc max (3000K)
3.28'	0.59'	2.40'	990.3
6.56'	1.18'	4.82'	247.6
9.84'	1.77'	7.22'	110.0
13.12'	2.36'	9.65'	61.9
16.40'	2.95'	12.04'	39.6

NEVA 4.0

S - 11°

H (ft)	Ø (ft)	fc max (3000K)
3.28'	0.62'	1841.8
6.56'	1.21'	460.4
9.84'	1.84'	204.7
13.12'	2.46'	115.1
16.40'	3.05'	73.7

M - 30°

H (ft)	Ø (ft)	fc max (3000K)
3.28'	1.64'	246.5
6.56'	3.25'	61.6
9.84'	4.89'	27.4
13.12'	6.53'	15.4
16.40'	8.17'	9.8

L - 45°

H (ft)	Ø (ft)	fc max (3000K)
3.28'	2.69'	157.1
6.56'	5.38'	39.3
9.84'	8.07'	17.5
13.12'	10.76'	9.8
16.40'	13.42'	6.3

W - 10°x40°

H (ft)	Ø (ft)	Ø (ft)	fc max (3000K)
3.28'	0.59'	2.40'	594.0
6.56'	1.18'	4.82'	148.5
9.84'	1.77'	7.22'	66.0
13.12'	2.36'	9.65'	37.2
16.40'	2.95'	12.04'	23.8

NEVA 5.0

S - 18°

H (ft)	Ø (ft)	fc max (white*)
3.28'	0.98'	203.5
6.56'	1.97'	50.7
9.84'	2.95'	22.9
13.12'	3.90'	12.8
16.40'	4.89'	8.4

M - 26°

H (ft)	Ø (ft)	fc max (white*)
3.28'	1.64'	68.6
6.56'	3.25'	11.7
9.84'	4.89'	7.8
13.12'	6.53'	4.5
16.40'	8.17'	2.8

L - 30°

H (ft)	Ø (ft)	fc max (white*)
3.28'	1.74'	140.9
6.56'	3.51'	35.2
9.84'	5.25'	15.7
13.12'	7.02'	8.8
16.40'	8.76'	5.7

W - 24°x46°

H (ft)	Ø (ft)	Ø (ft)	fc max (white*)
3.28'	1.41'	2.82'	105.6
6.56'	2.82'	5.61'	26.4
9.84'	4.27'	8.43'	11.7
13.12'	5.68'	11.22'	6.6
16.40'	7.09'	14.04'	4.2

* White created by mixing the colors

NEVA 6.0

S - 15°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	0.89'	1408.9
6.56'	1.77'	352.2
9.84'	2.62'	156.5
13.12'	3.51'	88.1
16.40'	4.40'	56.4

M - 26°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	1.54'	401.5
6.56'	3.08'	100.3
9.84'	4.63'	44.6
13.12'	6.17'	25.1
16.40'	7.68'	16.0

L - 30°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	1.74'	318.1
6.56'	3.51'	79.5
9.84'	5.25'	35.3
13.12'	7.02'	19.9
16.40'	8.76'	12.6

W - 24°x46°

H (ft)	Ø (ft)	Ø (ft)	fc max (4000K)
3.28'	1.41'	2.82'	281.9
6.56'	2.82'	5.61'	70.4
9.84'	4.27'	8.43'	31.4
13.12'	5.68'	3,42	17.7
16.40'	7.09'	4,28	11.3

NEVA 7.0

S - 18°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	1.02'	695.8
6.56'	2.03'	173.9
9.84'	3.05'	77.3
13.12'	4.07'	43.5
16.40'	5.09'	27.9

M - 32°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	1.84'	236.6
6.56'	3.67'	59.2
9.84'	5.51'	26.3
13.12'	7.35'	14.8
16.40'	9.19'	9.5

L - 44°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	2.62'	117.9
6.56'	5.28'	29.5
9.84'	7.91'	13.1
13.12'	10.53'	7.3
16.40'	13.19'	4.7

K - 78°

H (ft)	Ø (ft)	fc max (4000K)
3.28'	5.28'	50.7
6.56'	10.56'	12.7
9.84'	15.81'	5.7
13.12'	21.10'	3.2
16.40'	26.38'	2.0

W - 26°x58°

H (ft)	Ø (ft)	Ø (ft)	fc max (4000K)
3.28'	1.54'	3.61'	126.8
6.56'	3.05'	7.22'	31.7
9.84'	4.59'	10.83'	14.1
13.12'	6.10'	14.44'	7.9
16.40'	7.64'	18.04'	5.1