

Technical features

IP65

IK10


NEW



601601-02P

# PERISCOPE 01

11.81" height "L-shape" bollard, for outdoor installation, one-side downward asymmetrical light distribution, phospho-chromatised and polyester powder coated extruded aluminum body. Tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver 120VAC - 0-10V Dimming or 120-277VAC - ON/OFF, with CREE "XP-G2" LED. IP65 rating.



Technical data

IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance extruded copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Screws	Stainless steel
Transformer	Electronic power supply 120VAC - 0-10V Dimming or 120-277VAC - ON/OFF 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M16 rubber grommet
Power cable	1.64' neoprene power cable included
Gross weight	7.72 lbs

601601P		PERISCOPE 01 - 7 WATT - NR. 4 x CREE "XP-G2" LED		
light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
<b>3000°K warm-white</b>				
high-power led	Asymmetric	805	115.00	
<b>4000°K warm-white</b>				
high-power led	Asymmetric	847	121.00	



**Colors options**

- Textured Grey RAL 9006
- Anthracite Grey RAL 7016
- Matte Black (on request)

601602P		PERISCOPE 01 - 14 WATT - NR.8 x CREE "XP-G2" LED		
light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
<b>3000°K warm-white</b>				
high-power led	Asymmetric	1,610	115.00	
<b>4000°K warm-white</b>				
high-power led	Asymmetric	1,694	121.00	



**Colors options**

- Textured Grey RAL 9006
- Anthracite Grey RAL 7016
- Matte Black (on request)




Technical features



601603-04P

# PERISCOPE 02

19.69" height "L-shape" bollard, for outdoor installation, one-side downward asymmetrical light distribution, phospho-chromatised and polyester powder coated extruded aluminum body. Tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver 120VAC - 0-10V Dimming or 120-277VAC - ON/OFF, with CREE "XP-G2" LED. IP65 rating.



Technical data

IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance extruded copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Screws	Stainless steel
Transformer	Electronic power supply 120VAC - 0-10V Dimming or 120-277VAC - ON/OFF 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M16 rubber grommet
Power cable	1.64' neoprene power cable included
Gross weight	9.92 lbs



601603P		PERISCOPE 02 - 7 WATT - NR. 4 x CREE "XP-G2" LED		
light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
<b>3000°K warm-white</b>				
high-power led	Asymmetric	805	115.00	
<b>4000°K warm-white</b>				
high-power led	Asymmetric	847	121.00	



**Colors options**

- Textured Grey  
RAL 9006
- Anthracite Grey  
RAL 7016
- Matte Black  
(on request)

601604P		PERISCOPE 02 - 14 WATT - NR.8 x CREE "XP-G2" LED		
light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
<b>3000°K warm-white</b>				
high-power led	Asymmetric	1,610	115.00	
<b>4000°K warm-white</b>				
high-power led	Asymmetric	1,694	121.00	



**Colors options**

- Textured Grey  
RAL 9006
- Anthracite Grey  
RAL 7016
- Matte Black  
(on request)




Technical features



601605-06P

# PERISCOPE 03

29.53" height "L-shape" bollard, for outdoor installation, one-side downward asymmetrical light distribution, phospho-chromatised and polyester powder coated extruded aluminum body. Tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver 120VAC - 0-10V Dimming or 120-277VAC - ON/OFF, with CREE "XP-G2" LED. IP65 rating.



Technical data

IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance extruded copper-free aluminum body
Coating	Polyester powder coating with phosphocromating pre-finish
Screws	Stainless steel
Transformer	Electronic power supply 120VAC - 0-10V Dimming or 120-277VAC - ON/OFF 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M16 rubber grommet
Power cable	1.64' neoprene power cable included
Gross weight	12.13 lbs





601605P		PERISCOPE 03 - 7 WATT - NR. 4 x CREE "XP-G2" LED		
light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
<b>3000°K warm-white</b>				
high-power led	Asymmetric	805	115.00	
<b>4000°K warm-white</b>				
high-power led	Asymmetric	847	121.00	



**Colors options**

 Textured Grey RAL 9006	 Anthracite Grey RAL 7016	 Matte Black (on request)
---	---	---

601606P		PERISCOPE 03 - 14 WATT - NR.8 x CREE "XP-G2" LED		
light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
<b>3000°K warm-white</b>				
high-power led	Asymmetric	1,610	115.00	
<b>4000°K warm-white</b>				
high-power led	Asymmetric	1,694	121.00	



**Colors options**

 Textured Grey RAL 9006	 Anthracite Grey RAL 7016	 Matte Black (on request)
---	---	---

