

Pipedo Open is a surface mounted luminaire with both upward and downward light made of AirCoral® that is suitable for indoor installation. It is available in 3000K with a 120° optic as standard.

TECHNICAL DATA

Wattage / Input	2 x 8W (120-277VAC)
Power Supply	Integral
Construction	Body: AirCoral®
CCT	3000K (2700K, 4000K on request)
CRI	>90
Delivered Lumens	1340 lm per beam (3000K)
Efficacy	167.5 lm/W per beam
Optics	120°
Finishes	AirCoral®
Fixture Dimensions	19.29" l x 5.12" w x 3.94" h
IP Rating	IP20
IK Rating	-

The body is made of AirCoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for AirCoral® calculator.

Additionally, AirCoral® is:

- Antibacterial.
- Antifungal.
- Scratch-resistant.
- Dust-resistant.
- Suitable for painting.
- LEED recognized material.


ORDERING INFORMATION

Example: BU2916.AC.US.

BU2916	AC	US
Model No.	Finish	
BU2916	AC - AirCoral®	US




Fixture Dimensions



PHOTOMETRIC DATA

Maximum Candela = 248.8



Job Name/Date:

Fixture Type Designation: