QUBO MAXI COB



datasheet

The Qubo Maxi COB is a square, outdoor LED floodlight suitable for installation on a façade/wall with a U-shaped fixing bracket allowing vertical adjustment of $+90^{\circ}$ / -40° . It has 3 standard finishes and 3 optics options.






TECHNICAL DATA

Wattage / Input	42W (120VAC)		
Power Supply	Integral 0-10V Dimming		
Construction	Body: Die-Cast Copper-Free Aluminum		
	Screws: Stainless Steel		
	Lens: Tempered, Safety Glass		
	Cable Length: 3.28" included		
ССТ	3000K, 4000K		
CRI	>80		
Lumen Output	4752 lm (3000K, 35°)		
Efficacy	113.1 lm/W (3000K, 35°)		
Optics	3 Standard (see below)		
Finishes	3 Standard, Custom RAL (see below)		
Fixture Dimensions	6.69" l x 6.69" w x 9.06" h		
Fixture Weight	9.92 lbs		
LED Source	1 COB CREE "CXB 2540" LED		
IP Rating	IP66		
Impact Rating	IK10		

Fixture Dimensions



ORDERING INFORMATION

Example: 101604P-30K-14-TG. Accessories ordered separately.

101604P	-	-	-
Model No.	ССТ	Optics	Finish
101604P	30K - 3000K 40K - 4000K	14 - 14° 35 - 35° 55 - 55°	TG - Textured Grey (RAL 9006) AG - Anthracite Grey (RAL 7016) MB - Matte Black (on request)

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

1 of 2

QUBO MAXI COB



datasheet

ACCESSORIES

Installation



Anti-Glare



AC074 Honeycomb Louver



AC078 Anti-Glare Visor



AC038 Tree Strap for Ring Series

PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation:

2 of 2