

Luminaire designed for floor an ground installation, suitable for power LED sources. It is composed of aluminum body submitted to anodizing treatment up to 18 microns, polyester powder coated to ensure durability over time and maximum resistance against atmospheric agents. The internal screen diffuser is in satin PMMA. The protection degree IP66 is ensured by a special waterproof cable gland. It is completed by tubular steel pole of support, with polyester powder coated fixing plate welded along all the circumference of the luminaire. Luminaire's installation is allowed thanks to screws for direct fixing to the ground or appropriate flush fixing counterplate in steel sheet with anchor bolts for concrete planting. Available only in 24VDC power supply. Equipped with a 3.28' long neoprene cable outgoing from the stem, for connection to the supply line through appropriate waterproof connection systems to be ordered separately.





SPIKE MEGA












TECHNICAL DRAWING










SPIKE MEGA

model	code	lamp	lumens		emission	
			3000K	4000K		
SPIKE MEGA 180	LM05.104365.US	LED 13.2W	1701	1857	180°	
SPIKE MEGA 360	LM05.104366.US	LED 26.4W	3402	3714	360°	

EXAMPLE OF HEAD CODE COMPOSITION

24VDC Electronic driver and connection systems to be ordered as accessories.



	Light beam	
.DI	diffused	
	LED Color	
.BP	3000K	
.BF	4000K	

ACCESSORIES

	code	size	
24VDC POLE BELO	OW GROUND		
<u></u>	LM20.104369	H137.80"	
24VDC POLE V	VITH PLATE		
118.11"	LM20.104370	H118.11"	

	code	size	
ANCHOR PLATE FO	R POLE		



LM20.101235

Ø7.87" H11.81"



EXAMPLE OF 24VDC STEM CODE COMPOSITION



Communication	Technology

.00	Remote	

FINISH

11111311	THE TOTAL CONTRACT OF				
color	code	color	code	color	code
	.01 / painted white		.02 / painted black		.03 / anodized aluminum
	.04 / painted cor-ten		.11 / painted anthracite		





